

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No **BH102**

SHEET **1** of **3**

REFERENCE No **H9411**

PROJECT GATEWAY UPGRADE PROJECT GEOTECHNICAL INVESTIGATION - NORTHERN SECTION

LOCATION CONTROL LINE: MCAO - Ch. 18420.2 - OFFSET 23.5 R COORDINATES 9642.6 E; 169040.0 N

PROJECT No FM2055 SURFACE R.L. 3.15 DATE STARTED 3/8/04 DATUM SETP

JOB No DATUM AHD DATE COMPLETED 4/8/04 DRILLER R & D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER Casing Wash Boring Core Drilling	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
0	3.15					SANDY GRAVEL - FILL Dark brown, moist.		GP						
1	2.55					SILTY CLAY - FILL (??) Dark grey to mottled brown, mostly firm.		OL						
2	1.95					Medium plasticity, slightly organic. SANDY CLAY - FILL (??) Brown, moist, soft.		SC				MC=41.1%, WD=1.78t/m3, DD=1.26t/m3	U50	
3	0.65					ESTUARINE (??) SILTY CLAY Dark grey to slightly mottled (top), moist, soft to firm.		CH				LL=58.4%, PI=31.6%, LS=15.6% APD=2.670t/m3 MC=64.8%, WD=1.64t/m3, DD=1.00t/m3	U50	
4	-1.20					SILTY SAND - ALLUVIUM Dark grey to brown, moist, mainly very loose to loose.						LL=50.6%, PI=27.2%, LS=13.8% APD=2.669t/m3 MC=60.2%, WD=1.66t/m3, DD=1.04t/m3	U50	
5														
6												99% passing 2.36mm sieve	N<1	SPT
7						Some gravel fraction from 7.0m to 7.25m.		SP-SM				12% passing 75um sieve	1,2,2 N=4	SPT
8						Becoming silty clayey with depth.						6% passing 2um sieve	N<1	SPT
9														
10	-6.85													

REMARKS SPT N values in clayey sandy gravel can overestimate density due to influence of coarser size gravel particles. Defect angles have been measured with respect to a horizontal plane.

LOGGED BY
D.Dobe & A.Dissanayake



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No **BH102**

SHEET **2** of **3**

REFERENCE No **H9411**

PROJECT **GATEWAY UPGRADE PROJECT GEOTECHNICAL INVESTIGATION - NORTHERN SECTION**

LOCATION **CONTROL LINE: MCAO - Ch. 18420.2 - OFFSET 23.5 R** COORDINATES **9642.6 E; 169040.0 N**

PROJECT No **FM2055** SURFACE R.L. **3.15** DATE STARTED **3/8/04** DATUM **SETP**

JOB No DATUM **AHD** DATE COMPLETED **4/8/04** DRILLER **R & D Drilling Pty Ltd**

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	-6.85		CORE REC %		SILTY SAND / SANDY SILT - ALLUVIUM Pale grey to mottled orange, moist, mainly medium dense to dense. Fine grained sand.						7,15,16 N=31	SPT
11												
12											5,9,9 N=18	SPT
13					More sandy around 13m.	SM					9,10,14 N=24	SPT
14												
15					Becoming more gravel towards bottom.						6,9,10 N=19	SPT
16	-12.75				SAND - ALLUVIUM Orange brown to brown, wet, medium dense. Medium to coarse sand becoming fine with depth.						8,8,9 N=17	SPT
17												
18						SP					2,5,6 N=11	SPT
19					Some gravel around 19m.						4,9,12 N=21	SPT
20	-16.85											

REMARKS **SPT N values in clayey sandy gravel can overestimate density due to influence of coarser size gravel particles. Defect angles have been measured with respect to a horizontal plane.**

LOGGED BY
D.Dobe & A.Dissanayake



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No **BH102**
SHEET **3** of **3**
REFERENCE No **H9411**

PROJECT **GATEWAY UPGRADE PROJECT GEOTECHNICAL INVESTIGATION - NORTHERN SECTION**
LOCATION **CONTROL LINE: MCAO - Ch. 18420.2 - OFFSET 23.5 R** COORDINATES **9642.6 E; 169040.0 N**
PROJECT No **FM2055** SURFACE R.L. **3.15** DATE STARTED **3/8/04** DATUM **SETP**
JOB No DATUM **AHD** DATE COMPLETED **4/8/04** DRILLER **R & D Drilling Pty Ltd**

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-16.85					CLAYEY SANDY GRAVEL - ALLUVIUM Pale brown to orange brown, moist, dense to very dense.								
21						Angular to subangular gravel sizing up to 40mm.		GC					24,20,30 N=50	SPT
22	-18.25					SANDSTONE FINE TO MEDIUM GRAINED, POORLY CEMENTED, MAINLY MASSIVE TO SLIGHTLY LAMINATED SEDIMENTARY ROCK.		HW					30/80,+- N>50	SPT
23	-19.85			(100)		SW : Grey to pale grey, mainly massive to slightly laminated, low to mainly medium to occasional high strength.							Is(50)=0.90 MPa Is(50)=0.54 MPa	o x
24						Defects - Generally rare. - Occasional drilling induced lamination partings <10 deg (1/2m). - Joint @ 60 deg(1/3m).							Is(50)=0.39 MPa Is(50)=0.50 MPa	o x
25						Defects are generally planar, rough, light with no alteration and ironstaining.								
26				100 (100)				SW					Is(50)=0.32 MPa Is(50)=0.49 MPa	o x
27													Is(50)=1.11 MPa Is(50)=0.42 MPa	o x
28	-24.85			100									Is(50)=0.86 MPa Is(50)=0.98 MPa	o x
29						Borehole terminated at 28m								
30														

REMARKS SPT N values in clayey sandy gravel can overestimate density due to inflence of coarser size gravel particles. Defect angles have been measured with respect to a horizontal plane.

LOGGED BY
D.Dobe & A.Dissanayake

Project: **Gateway Upgrade Project Geotechnical Investigation**
Borehole No: **BH 102**
Start Depth: 23.00m
Finish Depth: 28.00m
Project No: FM2055
H No: 9411

