

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



**Queensland  
Government**

Department of  
Main Roads

# ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No BH4

SHEET 1 of 2

REFERENCE No H9784

PROJECT Caboolture River Bridge Foundation Investigation

LOCATION Pier 3 - 14.3m left (along skew) of existing northbound bridge C/L

COORDINATES 497553.8 E; 7003505.6 N

PROJECT No FG5439

SURFACE R.L. 3.00

DATE STARTED 08/11/05

DATUM MGA94 Zone 56

JOB No 25/10A/60C

DATUM AHD

DATE COMPLETED 08/11/05

DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	3.00											
1						<b>Sandy CLAY (Alluvium):</b> Brown, moist, soft, medium plasticity, fine grained sand.						
2							CI				Su = 32 kPa (PP)	1,1,2 N=3 SPT
3						High plasticity and some medium grained sand below 2.6m. Numerous orange iron-cemented nodules below 2.5m.					8/11/05	1,2,1 N=3 SPT
4	-0.90					<b>Clayey Gravelly SAND (Alluvium):</b> Grey-brown, moist, medium dense, fine to coarse grained, fine to medium angular gravel up to 20mm, high plasticity clay lenses.	SP					7,6,6 N=12 SPT
5	-2.00					<b>Gravelly SAND (Alluvium):</b> Pale grey-brown, moist, loose, medium to coarse grained, fine angular gravel up to 5mm.						5,4,4 N=8 SPT
6							SP					
7	-4.25					More gravel and less sand at base of unit. Gravel up to 30mm.						13,18,30/50 N=50 SPT
8	-5.00					<b>SANDSTONE:</b> HW: Dark orange-brown, medium grained, very low to low strength, subhorizontal bedding laminations.	HW				7.5m: Blade refusal. 7.5m-8.0m: Rock roller.	
9						MW: Pale orange-brown, medium grained, low to high strength, ironstained & iron cemented orange-brown throughout rockmass, occasional subhorizontal dark brown carbonaceous laminae and black vitreous coal laminae up to 20mm thick, and gravelly lenses throughout.					Pile Tip - 5.0	Is(50)=1.54 MPa Is(50)=1.87 MPa x o
10	-7.00					Less orange-brown iron staining and cementation 9.5-10.15m.	MW				9.75-10.15m: Grey sandstone with only slight ironstaining.	

REMARKS

LOGGED BY  
A O'Rourke



Queensland  
Government

Department of  
Main Roads

## ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No BH4

SHEET 2 of 2

REFERENCE No H9784

PROJECT Caboolture River Bridge Foundation Investigation

LOCATION Pier 3 - 14.3m left (along skew) of existing northbound bridge C/L

COORDINATES 497553.8 E; 7003505.6 N

PROJECT No FG5439

SURFACE R.L. 3.00

DATE STARTED 08/11/05

DATUM MG94 Zone 56

JOB No 25/10A/60C

DATUM AHD

DATE COMPLETED 08/11/05

DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
10	-7.00					<b>SANDSTONE:</b> As above. MW: Defects: Numerous subhorizontal to 20° planar bedding partings.  Only minor orange-brown staining between 10.8 - 11.15m. Gradation to SW sandstone.	MW				Is(50)=0.07 MPa Is(50)=0.16 MPa	x	o
11	-8.50		100 (58)			SW: Grey, some orange-brown iron staining, medium to coarse grained, low to medium strength. Numerous black coal laminae up to 20mm thick between 11.85 to 13.82m.	SW				Is(50)=0.32 MPa	o	
12						Iron cemented between 12.5 - 13.65m.					11.44-12.5m: Grey sandstone with only minor orange-brown ironstaining.  Total water loss into rock fractures below 12.5m.		
13						Numerous fine gravel lenses below 13.07m.					Is(50)=1.21 MPa Is(50)=1.52 MPa	x	o
14	-11.00		100			Borehole terminated at 14m					13.23-13.25m: Dark brown carbonaceous laminae. 13.67-13.68m: Black coal laminae.		
15													
16													
17													
18													
19													
20													

REMARKS

LOGGED BY  
A O'Rourke

ENGINEERING BOREHOLE CABOOLTURE R BRIDGE WIDENINGS GPJ QLD MAIN ROADS.GDT 23/02/06



Project: FOUNDATION INVESTIGATION FOR THE WIDENING OF THE CAPTAIN WHISH BRIDGES (NORTH AND SOUTHBOUND) - CABOOLTURE RIVER  
Borehole No: BH4 Pier 3  
Start Depth: 8.00m  
Finish Depth: 14.00m  
Project No: FG5439  
H No: 9784

START 8.00m



FG 5439 CAPTAIN WHISH BRIDGE PIER 3 BH4  
MID-Run 11.00m

H 9784 1/2 MID-Run 11m ↑



FG 5439 CAPTAIN WHISH BRIDGE PIER 3 BH4

H 9784 End of Run 14m ↑



SCALE 1:5

F:GEOT043/1

# Point Load Strength Index - Test Report

**Project: CABOOLTURE RIVER BRIDGE**

**Project No: FG 5439**

**Date Sampled 8/11/05**

**Feature: PIER 3**

**Sample Type: NMLC ROCK CORE**

**Date Tested 2/12/05**

**Report No. FG 5439/2/GS05/793AS4133.4.1**

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS05/793-A	BH4	8.05	D	1.55	1.54	H	Sandstone
GS05/793-B	BH4	8.08	A	2.17	1.87	H	Sandstone
GS05/793-C	BH4	9.96	D	0.08	0.07	VL	Sandstone
GS05/793-D	BH4	9.99	A	0.19	0.16	L	Sandstone
GS05/793-E	BH4	11.46	A	0.33	0.32	M	Sandstone
GS05/793-F	BH4	12.89	D	1.22	1.21	H	Sandstone
GS05/793-G	BH4	12.92	A	1.69	1.52	H	Sandstone

Sample Remarks

\* D - Diametral; A - Axial; B - Block; I - Irregular;

\*\* EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High ( taken from AS1726 Table 8A )

Remarks / Variations to Test Procedures:

Test Method: AS4133.4.1


Software Version 2.03 April 2005

Client Name: RS&E STRUCTURES DIVISION

Client Address: PO BOX 1412 SPRING HILL 4001

Signatory

( P.REYNOLDS )



Accreditation Number: 2302  
Accredited for compliance  
with ISO/IEC 17025

This document is issued in  
accordance with NATA's  
accreditation requirements.