

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH308**
SHEET **1** of **3**
REFERENCE No **11486**

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464697.2 E; 7871566.1 N
PROJECT No FG6020 SURFACE R.L. 11.30m PLUNGE _____ DATE STARTED 1/5/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/5/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	11.30												
1	11.10				A	Silty SAND (TOPSOIL) Pale brown, moist, loose. Fine to medium grained sand. Some tree roots.						6,11,14 N=25	SPT
2	9.60				B	Silty SAND Pale brown, moist, medium dense. Fine to medium grained sand.	(SM)					6,8,14 N=22	SPT
3					C	Sandy SILT Brown, moist, very stiff to hard. Low plasticity. Fine grained sand.						5,20,30 N=50	SPT
4					D	Becoming dry and hard.	(ML)					30/105mm N>50	SPT
5					E	Thin gravel layer, subangular, fine to medium grained.						23,29,30/120mm N>50	SPT
6	5.80				F	Silty SAND Pale brown, moist, dense to very dense. Medium to coarse grained sand.						24,30/70mm N>50	SPT
7					G		(SM)					15,17,24 N=41	SPT
8					H	Silt content increasing and becoming sandy silt in parts. Becoming fine grained sand.						12,17,23 N=40	SPT
9	1.70												
10	1.30					Sandy SILT (See over)	(ML)						

REMARKS _____

LOGGED BY
JA

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH308**
SHEET **2** of **3**
REFERENCE No **11486**

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464697.2 E; 7871566.1 N
PROJECT No FG6020 SURFACE R.L. 11.30m PLUNGE _____ DATE STARTED 1/5/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/5/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	1.30												
11					J	Sandy SILT (Cont'd) Dark brown, moist, hard. Low plasticity. Fine grained sand.		(ML)				11,15,23 N=38	SPT
12	-0.20				K	Silty SAND Dark brown, moist, medium dense to dense. Fine grained sand.						12,13,17 N=30	SPT
13					L							11,14,20 N=34	SPT
14													
15					M	Sand content increasing and becoming medium grained.		(SM)				11,11,15 N=26	SPT
16					N							9,14,17 N=31	SPT
17	-6.10												
18	-6.70					VOLCANIC BRECCIA Pyroclastic rock consisting of angular fragments embedded in a finer grained matrix. XW: Generally exhibits the engineering properties of pale grey, red and brown, moist, very dense silty sand. Medium to coarse grained.		HW				30/20mm N>50	SPT
19			(17)			HW: Red, brown, pink, medium to coarse grained, massive, mainly very low to low strength with medium to high strength core stones.		HW				Is(50) = 1.71MPa	o
20	-8.70		100 (13)									Is(50) = 0.08MPa	o
			100 (0)										
			100 (0)										
			100 (0)										

REMARKS _____

LOGGED BY
JA

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH308**
SHEET **3** of **3**
REFERENCE No **11486**

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464697.2 E; 7871566.1 N
PROJECT No FG6020 SURFACE R.L. 11.30m PLUNGE _____ DATE STARTED 1/5/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/5/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
20	-8.70		(0) 100		VOLCANIC BRECCIA HW: (Cont'd) Defects: - Broken and clayey throughout. Defects are generally irregular, rough, open, clay infilled.	+		EH VH H M J VL EL		20 60 200 600 2000		Clay seam Is(50) = 0.34MPa	o	
21	-9.76		(0) 100		MW: Pink, grey, brown, medium to coarse grained, massive, medium to mainly high strength. Defects: - HW broken zones <200mm - Joint @ 20°-30° (3-4/m) - Joint @ 50°-60° (2-3m) - Joint @ 70° (1/m)	+						Is(50) = 0.21MPa	o	
22			(0) 100			+						Is(50) = 0.63MPa	o	
23			(73) 100		Defect spacing is mainly medium. Defect surfaces are planar or irregular, rough, open, clay infilled.	+						Is(50) = 3.07MPa Is(50) = 0.81MPa	o	
24			(62) 100			+						Is(50) = 3.03MPa Is(50) = 1.44MPa UCS=48.7MPa	o	
25						+						Is(50) = 2.09MPa	o	
26						+						Is(50) = 1.49MPa	o	
26.6	-15.30		100		Borehole terminated at 26.6m	+						Is(50) = 1.06MPa	o	
27														
28														
29														
30														

REMARKS _____

LOGGED BY
JA

CORE PHOTO LOG

DEPARTMENT OF TRANSPORT & MAIN ROADS
Geotechnical Branch
35 Butterfield Street, HERSTON Qld 4006
Phone 07 3066 3336



Department of
Transport and Main Roads

