

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>





# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH16  
SHEET 1 of 2  
REFERENCE No H11026

PROJECT Moreton Bay Rail Link  
LOCATION Cut 6, Ch.6260 COORDINATES 503011.6 E; 6986682.7 N  
PROJECT No FG5921 SURFACE R.L. 30.10m PLUNGE \_\_\_\_\_ DATE STARTED 6/5/11 GRID DATUM MGA94 Zone 56  
JOB No 250/120/3 HEIGHT DATUM AHD BEARING \_\_\_\_\_ DATE COMPLETED 6/5/11 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING CORE DRILLING	RQD ( ) %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	30.10										Based on Driller's logs only	
29.90					<b>Silty CLAY (Topsoil)</b> Dark grey, moist, soft.							
					<b>Sandy CLAY (Residual)</b> Cream white with orange red mottles, fine to medium grained, moist, stiff to very stiff.							
1				A	High plasticity. Iron stained nodules.	(CH)					2,3,14 N=17	SPT
28.10				B	<b>Quartz Feldspathic SANDSTONE</b> Medium to coarse grained, massive, poorly cemented sedimentary rock mainly comprising sand-sized particles <b>HW:</b> Red with white, black and red mottles, medium grained, very low to low strength.						18,10/0mm, HB N>50	SPT
			(93)		Exhibits engineering properties of silty sand. Becoming red and grey white, fine to medium grained, massive, slightly laminated, very low to low strength.						Is(50) = 0.33MPa Is(50) = 0.30MPa	x o
			100 (100)		Contains frequent thin bands of coarse grained sand sizing <2mm.						Is(50) = 1.95MPa	x
			100 (93)		Defects: - Drilling-induced partings @ 5-10° (2-9/m) - Subhorizontal joint @ 20° (1-2/m)	HW					Is(50) = 0.27MPa Is(50) = 0.38MPa	x o
			100 (71)		Defect surfaces are mainly wide to very widely spaced, irregular, planar, slightly rough, open, clean and iron stained.						Is(50) = 0.19MPa Is(50) = 0.29MPa	x o
					Becoming yellow below 5m.						Is(50) = 1.02MPa Is(50) = 0.91MPa	x o
22.10			100 (86)		<b>MW:</b> Green white with black, red brown, grey and white mottles, fine to coarse grained, massive, low strength.						Is(50) = 0.27MPa Is(50) = 0.15MPa	x o
					Coarse grained lithic sandstone below 9.8m.	MW					Coarse grained lithic SS 450mm thick	
											PROPOSED RAIL LEVEL	
10			100		(See over)							

REMARKS \_\_\_\_\_

LOGGED BY  
BW / JSM





# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH16

SHEET 2 of 2

REFERENCE No H11026

PROJECT Moreton Bay Rail Link

LOCATION Cut 6, Ch.6260 COORDINATES 503011.6 E; 6986682.7 N

PROJECT No FG5921 SURFACE R.L. 30.10m PLUNGE      DATE STARTED 6/5/11 GRID DATUM MGA94 Zone 56

JOB No 250/120/3 HEIGHT DATUM AHD BEARING      DATE COMPLETED 6/5/11 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING CORE DRILLING	RQD ( ) %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH					DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
										EH	VH	IN	N	VL	EL				
10	20.10																		
11			(1)			<b>Quartz Feldspathic SANDSTONE</b> <b>MW: (Cont'd)</b> Grey white, red and yellow scattered, fine grained, clay matrix.  Iron staining throughout.  Defects: - Drilling-induced partings @ 5-10° (3/m)											Is(50) = 0.16MPa Is(50) = 0.14MPa DD = 1.97t/m <sup>3</sup> ; MC = 7.8%; UCS=1MPa	x	UCS
12			100 (87)			Defect surfaces are medium to widely spaced, irregular and steeped, rough, open and clean, iron stained.											Is(50) = 0.18MPa	o	
13			100 (100)																
14			100 (100)				MW										Is(50) = 0.16MPa Is(50) = 0.10MPa DD = 2.10t/m <sup>3</sup> ; MC = 6.3%; UCS=3.21MPa	x o	UCS
15			100 (100)														Is(50) = 0.52MPa Is(50) = 0.75MPa	x o	
16			100 (100)														Is(50) = 0.27MPa Is(50) = 0.23MPa	x o	
17			100														Is(50) = 0.17MPa Is(50) = 0.24MPa	x o	
17.45	12.65		100														Fine grained SST Is(50) = 0.33MPa Is(50) = 0.40MPa	x x	
18						Borehole terminated at 17.45m													
19																			
20																			

REMARKS

LOGGED BY  
BW / JSM







<b>Project Name</b>	<b>Moreton Bay Rail Link (MBRL)</b>		
<b>Project No</b>	FG5921	<b>Date</b>	06/05/11
<b>Borehole No</b>	BH 16	<b>TMR H No</b>	11026
<b>Location</b>	Cut	<b>Start Depth (m)</b>	2.5
<b>Detail</b>	Cut	<b>Finish Depth (m)</b>	17.45
<b>Chainage</b>	Approx	<b>Submitted By</b>	BW
<b>Remarks</b>			

  

  

0 100 200 300 400 500 600mm

SCALE 1:5