

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH404**
SHEET **1** of **4**
REFERENCE No **H11492**

PROJECT Townsville Ring Road Section 4
LOCATION Geaney Lane Overpass COORDINATES 464706.1 E; 7871666.1 N
PROJECT No FG6020 SURFACE R.L. 14.10m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	14.10		CORE REC %				EH VH H M L VL EL		20 60 200 600 2000			
1				A	Clayey SAND (FILL) Dark grey to brown, moist, loose to medium dense.	(SC)					1,5,4 N=9	SPT
2	12.20			B							4,4,8 N=12	SPT
3				C	Clayey SAND Pale brown to brown, slightly moist to moist, very dense. Generally fine to medium grained sand with coarse grained bands throughout.						30/50 N>50	SPT
4				D							30/100 N>50	SPT
5				E		(SC)					12,23,30/100 N>50	SPT
6				F							30/150 N>50	SPT
7				G							28,30/60 N>50	SPT
8												
9	5.10			H	Sandy CLAY Pale brown with occasional orange brown ironstaining, slightly moist, hard. Low plasticity, fine to medium grained sand.	(CL)					30/150 N>50	SPT
10												

REMARKS _____

LOGGED BY
VP

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH404**
SHEET **2** of **4**
REFERENCE No **H11492**

PROJECT Townsville Ring Road Section 4
LOCATION Geaney Lane Overpass COORDINATES 464706.1 E; 7871666.1 N
PROJECT No FG6020 SURFACE R.L. 14.10m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	4.10												
11					J	Sandy CLAY (Cont'd)						18,30/110 N>50	SPT
12					K	Trace fine gravel.	(CL)					12,30/150 N>50	SPT
13	0.90												
14					L	Clayey SAND Pale brown with some orange brown iron staining in part, moist, dense to mainly very dense. Medium to coarse grained sand.						13,26,30/105 N>50	SPT
15					M							10,17,26 N=43	SPT
16													
17					N	Becoming fine to medium grained sand.	(SC)					14,25,30/110 N>50	SPT
18					P	Becoming medium to coarse grained sand.						23,30/110 N>50	SPT
19	-4.60												
20					Q	VOLCANIC BRECCIA Pyroclastic rock consisting of angular fragments embedded in a finer grained matrix. XW: Generally exhibits the engineering properties of a pale brown, moist, hard, Sandy Gravelly Clay. Low plasticity.	XW					14,30/140 N>50	SPT

REMARKS _____

LOGGED BY
VP

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH404**
SHEET **3** of **4**
REFERENCE No **H11492**

PROJECT Townsville Ring Road Section 4
LOCATION Geaney Lane Overpass COORDINATES 464706.1 E; 7871666.1 N
PROJECT No FG6020 SURFACE R.L. 14.10m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-5.90													
21					R	VOLCANIC BRECCIA XW:(Cont'd) Becoming pale brown, red, moist, very dense, Clayey Gravelly Sand.							27,30/130 N>50	SPT
22						Becoming brown, brown to red, pink, moist, very dense Gravelly Sand. HW rock fragments.							30/50 N>50	SPT
23							XW						30/50 N>50	SPT
24													30/50 N>50	SPT
25														
26	-11.40		(0)		U	HW: Pale brown, pink, red, medium to coarse grained, massive, generally very low to low strength. Defects: -Joint at 60°-70° (3/m) -Irregular Joints (3/m) Defects are generally planar to irregular, rough, open, clayey infilled. Defect spacing: Close to medium.							30/50 N>50 Is(50) = 0.31MPa	SPT
27	-12.75		100 (0)			MW: Brown to red, pink, fine to coarse grained, massive, medium to mainly high strength. Clasts (sizing from 2mm to 30mm diameter) in a finer grained matrix. Defects: -Joint at 0°-30° (1/m) -Joint at 45° (1/m) -Joint at 60°-70° (2/m) Defects are generally planar, rough, open, clayey infilled. Defect spacing: Mainly medium to wide.							Is(50) = 0.11MPa	o
28			100 (40)				MW						Is(50) = 0.42MPa	o
29													Is(50) = 1.58MPa	o
30													Is(50) = 1.95MPa	o
													Is(50) = 1.56MPa	o

REMARKS _____

LOGGED BY
VP

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH404**
SHEET **4** of **4**
REFERENCE No **H11492**

PROJECT Townsville Ring Road Section 4
LOCATION Geaney Lane Overpass COORDINATES 464706.1 E; 7871666.1 N
PROJECT No FG6020 SURFACE R.L. 14.10m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
30	-15.90					VOLCANIC BRECCIA MW: (Cont'd)	△						UCS=13.7 MPa	
31				100 (20)			△						Is(50) = 2.23MPa	o
	-17.30					ANDESITE: Fine grained, intermediate extrusive igneous rock.	▽						Is(50) = 4.59MPa	o
32						MW: Brown, fine grained, massive, medium to mainly high strength.	▽							
						Defects:	▽							
						-Joint at 0°-30° (2/m)	▽							
						-Joint at 40°-50° (3/m)	▽							
						-Joint at 60°-70° (2/m)	▽							
						Defects are generally planar, rough, open.	▽						Is(50) = 1.79MPa	o
						Defect spacing: medium	▽							
33	-18.90			100		Borehole terminated at 33m								
34														
35														
36														
37														
38														
39														
40														

REMARKS _____

LOGGED BY
VP

CORE PHOTO LOG

DEPARTMENT OF TRANSPORT & MAIN ROADS
Geotechnical Branch
35 Butterfield Street, HERSTON Qld 4006
Phone 07 3066 3336



Department of
Transport and Main Roads

Project Name	Townsville Ring Road Section 4		
Project No	FG 6020	Date	21/04/13
Borehole No	BH 404	TMR H No	11492
Location	Geaney Lane Overpass	Start Depth (m)	25.50
Detail	Pier 1 (Left)	Finish Depth (m)	33.00
Chainage		Submitted By	MS
Remarks			

