

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH406**  
SHEET **1** of **3**  
REFERENCE No **H11494**

PROJECT Townsville Ring Road Section 4  
LOCATION Geaney Lane Overpass COORDINATES 464708.1 E; 7871691.0 N  
PROJECT No FG6020 SURFACE R.L. 13.22m PLUNGE \_\_\_\_\_ DATE STARTED 23/4/13 GRID DATUM GDA 94  
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING \_\_\_\_\_ DATE COMPLETED 29/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	CASING OTHER WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	13.22					<b>Engineered Road Base and Fill</b>							
1												Non Destructive Digging Techniques Used.	
1.72						<b>Clayey SAND</b> Pale brown to brown, moist, dense to very dense. Medium to coarse grained sand.							
2					C		(SC)					12,19,20 N=39	SPT
3					D	Trace gravel, angular.						17,30/100 N>50	SPT
3.22						<b>Silty SAND</b> Brown, moist, very dense. Fine to medium grained sand.							
4	9.22				E							28,30/75 N>50	SPT
5							(SM)						
6					F							18,29,30/125 N>50	SPT
7	6.22				G	<b>Clayey SAND</b> Pale brown to brown, moist, dense to mainly very dense. Medium to coarse grained sand.						18,30/130 N>50	SPT
8							(SC)						
9					H							12,21,30 N>50	SPT
10													

REMARKS \_\_\_\_\_

LOGGED BY  
VP

# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH406**  
SHEET **2** of **3**  
REFERENCE No **H11494**

PROJECT Townsville Ring Road Section 4  
LOCATION Geaney Lane Overpass COORDINATES 464708.1 E; 7871691.0 N  
PROJECT No FG6020 SURFACE R.L. 13.22m PLUNGE \_\_\_\_\_ DATE STARTED 23/4/13 GRID DATUM GDA 94  
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING \_\_\_\_\_ DATE COMPLETED 29/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	CASING OTHER WASH BORING CORE DRILLING	RQD (%)	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	3.22											
11				J	Clayey SAND (Cont'd) Becoming dense.						13,23,23 N=46	SPT
12				K	Becoming very dense & iron stained.						11,21,30/140 N>50	SPT
13												
14				L	Becoming medium dense to dense.						7,13,17 N=30	SPT
15				M	Becoming medium to coarse grained sand.						10,15,18 N=33	SPT
16												
17				N	Becoming fine to medium grained & very dense sand.						20,28,30/120 N>50	SPT
18	-4.98			P							28,30/140 N>50	SPT
19	-6.28		(32)	Q	<b>VOLCANIC BRECCIA</b> Pyroclastic rock consisting of angular fragments embedded in a finer grained matrix. <b>XW:</b> Generally exhibits the engineering properties of a red, pink brown to yellow brown to grey, slightly moist, Clayey Sand. Some fine grained gravel. <b>MW:</b> Red, pink brown, medium to coarse grained, massive, low to medium strength.		XW				30/30 N>50 Is(50) = 0.17MPa	SPT
20							MW					

REMARKS \_\_\_\_\_

LOGGED BY  
VP

# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH406**  
SHEET **3** of **3**  
REFERENCE No **H11494**

PROJECT Townsville Ring Road Section 4  
LOCATION Geaney Lane Overpass COORDINATES 464708.1 E; 7871691.0 N  
PROJECT No FG6020 SURFACE R.L. 13.22m PLUNGE \_\_\_\_\_ DATE STARTED 23/4/13 GRID DATUM GDA 94  
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING \_\_\_\_\_ DATE COMPLETED 29/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	CASING OTHER WASH BORING CORE DRILLING	RQD ( ) %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	INTACT STRENGTH							DEFECT SPACING (mm)			GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS			
							WEATHERING							EL						2000		
							USC	EH	VH	H	M	L	EL	20	60	200				600	2000	
20	-6.78				<b>VOLCANIC BRECCIA</b>	Δ																
	-7.03				<b>MW: (Cont'd)</b>	Δ	MW															
					<b>HW:</b> Red, pink brown, grey, medium to coarse grained, massive, very low to low strength.	Δ	HW															
					XW zones with very low strength up to 30cm.	Δ	XW															
21			100		Defects:	Δ																
			(28)		Broken throughout, clayey infilled joints.	Δ																
	-8.63				Defect spacing: Close	Δ	HW															
22					<b>MW:</b> Red, pink brown, yellow, medium to coarse grained, massive, mainly medium strength. Some HW patches with very low to low strength.	Δ																
					Defects:	Δ																
					- Joints @ 20°-30° (2/m)	Δ	MW															
					- Joints @ 40°-50° (5/m)	Δ																
23			100		- Joints @ 60°-70° (2/m)	Δ																
			(8)		- Irregular joints (3/m)	Δ																
					Defects are generally planar to irregular, rough, open, clay infilled.	Δ																
					Defect spacing: Close to mainly medium.	Δ	HW															
24						Δ																
			100			Δ																
25			(0)			Δ	MW															
						Δ																
						Δ																
			93			Δ																
26	-12.78		(0)		<b>ANDESITE: Fine grained, intermediate extrusive igneous rock.</b>	Δ	HW															
					<b>MW:</b> Dark brown, fine grained, massive, low strength.	Δ																
					Defects:	Δ																
			93		- Joints @ 20°-30° (5/m)	Δ	MW															
27			(72)		- Joints @ 50°-60° (5/m)	Δ																
	-14.08				Defects are generally planar, rough, iron stained, open.	Δ																
					Defect spacing: Close to medium.	Δ																
28					<b>SW:</b> Dark grey to black, fine grained, massive, high to very high strength.	Δ	SW															
					Defects:	Δ																
					- Joints @ 45° (1/m)	Δ																
					- Joints @ 60° - 70° (1/m)	Δ																
	-15.28		100		Defects are generally planar, rough, iron stained, open.	Δ																
					Defect spacing: Mainly wide.	Δ																
29					Borehole terminated at 28.5m	Δ																

REMARKS \_\_\_\_\_

LOGGED BY  
VP



# CORE PHOTO LOG

DEPARTMENT OF TRANSPORT & MAIN ROADS  
Geotechnical Branch  
35 Butterfield Street, HERSTON Qld 4006  
Phone 07 3066 3336



Department of  
Transport and Main Roads

Project Name	Townsville Ring Road Section 4		
Project No	FG 6020	Date	29/04/13
Borehole No	BH 406	TMR H No	11494
Location	Geaney Lane Overpass	Start Depth (m)	19.50
Detail	Pier 2 (Left)	Finish Depth (m)	28.50
Chainage		Submitted By	MS
Remarks			

  

0 100 200 300 400 500 600 700

SCALE 1:5