

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://ggd.org.au/>



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No **BHP83**

SHEET **1** of **2**

REFERENCE No **H9915**

PROJECT **HOUGHTON HIGHWAY BRIDGE DUPLICATION - HOUGHTON HIGHWAY UPGRADE PROJECT**

LOCATION **24m RIGHT FROM EASTN PILE OF PIER 83 OF EXIST BRIDGE** COORDINATES **39850.1 E; 53988.6 N**

PROJECT No **FG5423** SURFACE R.L. **-1.21** PLUNGE DATE STARTED **05/06/06** GRID DATUM **PROJECT DATUM**

JOB No **165/122/35** HEIGHT DATUM **AHD** BEARING DATE COMPLETED **05/06/06** DRILLER **CAIRNS DRILLING**

DEPTH (m)	R.L. (m)	CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	-1.21												
0.5					A	ESTUARINE SAND Dark grey, wet, mainly very loose.						pH _F = 7.48 pH _{FOX} = 6.31	HW, 1,1 N=2 ASS Sample stored at Herston Geotechnical Laboratory
1.5					B	Fine grained sand with partly decomposed shell fragments throughout; slightly organic throughout.						pH _F = 7.49 pH _{FOX} = 6.67	1, 1 N=1
2.5					C	High amount of shell at 3m.						pH _F = 8.02 pH _{FOX} = 6.35	RW, HW N<1 ASS Sample stored at Herston Geotechnical Laboratory
3.5					D		(SM)					pH _F = 7.95 pH _{FOX} = 5.57	RW N<1
4.5					E							pH _F = 7.46 pH _{FOX} = 5.78	RW N<1 ASS Sample stored at Herston Geotechnical Laboratory
5.5					F	ESTUARINE SILTY SAND/CLAYEY SAND Dark grey, wet, very loose to loose.						pH _F = 7.89 pH _{FOX} = 4.75	RW N<1 ASS Sample stored at Herston Geotechnical Laboratory
6.5					G	ESTUARINE GRAVELLY CLAY Dark grey, wet, very soft to soft.						pH _F = 7.79 pH _{FOX} = 6.02	1, 2, 2 N=4 ASS Sample stored at Herston Geotechnical Laboratory
7.5													
8.5													
9.5													
10.5													
11.5													
12.5													
13.5													
14.5													
15.5													
16.5													
17.5													
18.5													
19.5													
20.5													
21.5													
22.5													
23.5													
24.5													
25.5													
26.5													
27.5													
28.5													
29.5													
30.5													
31.5													
32.5													
33.5													
34.5													
35.5													
36.5													
37.5													
38.5													
39.5													
40.5													
41.5													
42.5													
43.5													
44.5													
45.5													
46.5													
47.5													
48.5													
49.5													
50.5													
51.5													
52.5													
53.5													
54.5													
55.5													
56.5													
57.5													
58.5													
59.5													
60.5													
61.5													
62.5													
63.5													
64.5													
65.5													
66.5													
67.5													
68.5													
69.5													
70.5													
71.5													
72.5													
73.5													
74.5													
75.5													
76.5													
77.5													
78.5													
79.5													
80.5													
81.5													
82.5													
83.5													
84.5													
85.5													
86.5													
87.5													
88.5													
89.5													
90.5													
91.5													
92.5													
93.5													
94.5													
95.5													
96.5													
97.5													
98.5													
99.5													
100.5													

REMARKS

LOGGED BY
BW / ADISS



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No **BHP83**

SHEET **2** of **2**

REFERENCE No **H9915**

PROJECT **HOUGHTON HIGHWAY BRIDGE DUPLICATION - HOUGHTON HIGHWAY UPGRADE PROJECT**

LOCATION **24m RIGHT FROM EASTN PILE OF PIER 83 OF EXIST BRIDGE** COORDINATES **39850.1 E; 53988.6 N**

PROJECT No **FG5423** SURFACE R.L. **-1.21** PLUNGE DATE STARTED **05/06/06** GRID DATUM **PROJECT DATUM**

JOB No **165/122/35** HEIGHT DATUM **AHD** BEARING DATE COMPLETED **05/06/06** DRILLER **CAIRNS DRILLING**

DEPTH (m)	R.L. (m)	CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	-11.21					RESIDUAL SANDY SILTY CLAY Mottled orange brown becoming white with depth, moist, stiff to very stiff.							
11					H	Consisting of highly lateritic and concreted zones in the upper area with some relic rock structures; becoming medium plastic white kaolinic clay with depth.						pH _s = 6.14 pH _{FOX} = 4.93	5,5,10 N=15 ASS Sample stored at Herston Geotechnical Laboratory
12					J			(CI)					3,4,8 N=12
13													
14					K								3,4,7 N=11
15	-16.01				L	SANDSTONE FINE TO MEDIUM GRAINED MAINLY MASSIVE TO SLIGHTLY LAMINATED POORLY CEMENTED SEDIMENTARY ROCK HW : Pale orange brown, moist, very dense silty sand gradually grading into very low to low strength rock.		HW					30/110 N>50
16	-17.71												
17					(100)	SW: Pale orange gradually becoming to pale grey/white, mainly massive, mainly fine to medium grained, mainly medium to high strength. Occasional carbonaceous laminations and rip-up clasts sizing upto 25mm. Defects: Generally rare with some drilling induced breaks.						Is(50)=0.68 MPa Is(50)=1.53 MPa Is(50)=1.34 MPa Is(50)=1.59 MPa Is(50)=0.52 MPa Is(50)=0.62 MPa	x o x o
18								SW				Is(50)=0.52 MPa Is(50)=0.65 MPa	x o
19												Is(50)=0.41 MPa Is(50)=0.38 MPa Is(50)=0.94 MPa Is(50)=1.01 MPa	o x x o
20	-20.71				100	Borehole terminated at 19.5m							

REMARKS

LOGGED BY
BW / ADISS

Project: **Houghton Highway Bridge Duplication**
Borehole No: **BHP83**
Start Depth: 16.50m
Finish Depth: 19.50m
Project No: FG5423
H No: 9915



0 100 200 300 400 500 600mm

SCALE 1:5

Point Load Strength Index - Test Report

Project: Houghton Highway Bridge Investigation

Project No: FG5423

Date Sampled 05/06/06

Feature: N/A

Sample Type: NMLC Core

Date Tested 10/06/06

Report No. FG5423/GS06-482/AS4133.4.1

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS06/482.A	BHP 83	16.72	D	0.68	0.68	M	Sandstone
GS06/482.B	BHP 83	16.75	A	1.47	1.53	H	Sandstone
GS06/482.C	BHP 83	16.82	D	1.34	1.34	H	Sandstone
GS06/482.D	BHP 83	16.85	A	1.56	1.59	H	Sandstone
GS06/482.E	BHP 83	17.37	D	0.53	0.52	M	Sandstone
GS06/482.F	BHP 83	17.39	A	0.62	0.62	M	Sandstone
GS06/482.G	BHP 83	18.10	D	0.52	0.52	M	Sandstone
GS06/482.H	BHP 83	18.13	A	0.65	0.65	M	Sandstone
GS06/482.J	BHP 83	18.92	D	0.38	0.38	M	Sandstone
GS06/482.K	BHP 83	18.90	A	0.43	0.41	M	Sandstone

Sample Remarks

* D - Diametral; A - Axial; B - Block; I - Irregular;

** EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High (taken from AS1726 Table 8A)

Remarks / Variations to Test Procedures:

Test Method: AS4133.4.1

Software Version 2.03 April 2005

Client Name: Department of Main Roads

Client Address: PO Box 70, Spring Hill QLD 4004

Signatory *P. Simson* 14/6/06

(Mr Peter Simson)



Accreditation Number: 2302
Accredited for compliance
with ISO/IEC 17025

This document is issued in
accordance with NATA's



Point Load Strength Index - Test Report

Project: Houghton Highway Bridge Investigation

Project No: FG5423

Date Sampled 05/06/06

Feature: N/A

Sample Type: NMLC Core

Date Tested 10/06/06

Report No. FG5423/GS06-482/AS4133.4.1

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS06/482.L	BHP 83	19.46	D	0.95	0.94	M	Sandstone
GS06/482.M	BHP 83	19.48	A	1.01	1.01	H	Sandstone

Sample Remarks

* D - Diametral; A - Axial; B - Block; I - Irregular;

** EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High (taken from AS1726 Table 8A)

Remarks / Variations to Test Procedures:

Test Method: AS4133.4.1

Software Version 2.03 April 2005

Client Name: Department of Main Roads

Client Address: PO Box 70, Spring Hill QLD 4004

Signatory

P. Simson 14.16.06

(Mr Peter Simson)



Accreditation Number: 2302
Accredited for compliance
with ISO/IEC 17025

This document is issued in
accordance with NATA's