#### **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

#### **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



TMR.GLB Log A\_ENGINEERING BOREHOLE LOG W LITHOLOGY JINGI JINGI BH LOGS.GPJ <<DrawingFile>> Datgel CPT Tool glint Add-In 18/12/2014 13:31

# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH12
SHEET	_1_ of _3_
REFERENCE No	11846

PRO	JECT	_Jingi_	Jingi Cree	ek Br	idgesite Investigation							
LOC	ATION	<u>Pier 1</u>	<u> 10 - Right</u>	<u>Han</u>	d Side				COORD	INATES <u>287030.2</u> <u>E; 7024325.5</u> <u>N</u>		
PROJECT No_FG6169			<u>69</u>	SURFACE R.L. 315.27m PLUNGE				DATE STARTED 2	7/6/14	GRID DATUM MGA 94 Zone 56		
JOB	No	222/1	8C/5		HEIGHT DATUM <u>AHD</u> BEARING			DATE COMPLETED 2	7/6/14	DRILLER North Coast Drilling		
o DEPTH(m)	R.L. (m)	AÜGER CASING WASH BORING CORE DRILLING		SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	INTACT DEFECT STRENGTH SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA  AND  TEST RESULTS  S WWS  WS  S  S  S  S  S  S  S  S  S		
0.40	314.87				Silty CLAY (TOPSOIL) Dark grey black, moist, soft. Low plasticity. Some sand, gravel and organic matter.  Silty CLAY (ALLUVIAL) Dark grey, moist, soft to firm.		(CL					
- -1 - - - - -				А	High plasticity. Trace organic matter.		(CH	)		1,2,2 N=4 SPT		
- -2 - - - - 2.50	312.77			В	2.00m: Becoming stiff.  Sandy CLAY (ALLUVIAL)			<u>+</u>		3,5,8 N=13		
- - - 3 - - - - - - 3.50	311.77			С	Grey, brown, moist, very stiff. Mainly low to medium plasticity. Some fine gravel.		(CL CI)			5,9,11 N=20 SPT		
- - - -4 - - - -				D	Clayey SAND (ALLUVIAL) Dark grey brown, moist, medium dense to dense. Fine to medium grained sand.		(SC			12,14,16 N=30 SPT		
5. <u>90</u>	310.27 309.37			E	Silty CLAY (ALLUVIAL) Dark grey, moist, very stiff. High plasticity.		(CH	)		7,9,11 N=20 SPT		
-6 - - - - -				F	Clayey SAND (ALLUVIAL) Pale grey brown, moist, dense to very dense. Fine to medium grained sand.		(00			11,13,21 N=34 SPT		
- 7 - - - - - - - - - - - - -	307.27			G			(SC	, ————————————————————————————————————		13,30/130mm SPT		
- - - - - - - - - - -				Н	CLAYSTONE (J_Kk) XW: Recovered as grey, dark brown, moist, hard, silty clay. Mainly low to medium plasticity. Some iron oxide precipitate.		xw			8,24,28 N=52 SPT		
- - - - - - - 10				J	9.00m: Colour change to pale cream, white. Low plasticity.					16,29,30/40mm SPT		
R	EMARK		= Kumba							LOGGED BY		
		* For	this spec	imer	n, the load cell used does not comply with the test	<u>meth</u>	od re	equirements.		MS		



### ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH12
SHEET	_2_ of _3_
REFERENCE No	11846

**PROJECT** Jingi Jingi Creek Bridgesite Investigation COORDINATES 287030.2 E; 7024325.5 N LOCATION Pier 10 - Right Hand Side SURFACE R.L. 315.27m PLUNGE DATE STARTED <u>27/6/14</u> PROJECT No\_FG6169\_ \_ \_ \_ GRID DATUM MGA 94 Zone 56 DATE COMPLETED 27/6/14 JOB No 222/18C/5 HEIGHT DATUM <u>AHD</u> \_\_ BEARING \_ \_ \_ \_ DRILLER North Coast Drilling INTACT DEFECT R.L. ROD STRENGTH SPACING ADDITIONAL DATA (m) ()% 90  $\widehat{\mathbb{E}}$ MATERIAL (mm) LITHOLOGY AND SAMPLES **DESCRIPTION** TESTS CORE **TEST RESULTS** REC % 10 CLAYSTONE (J\_Kk) Κ 14,30/145mm SPT XW: (Cont'd) 8,14,16 SPT 12 XW SPT 15,22,30/140mm 13 N 30/130mm SPT - 14 30/100mm SP1 301.07 (71) CLAYSTONE (J\_Kk) Datgel CPT Tool glNt Add-In HW: White, yellow, dark brown patches, HW fine grained, medium bedded, mainly very UCS UCS=527kPa low strength. Some XW weathered zones. 14.90m-15.20m: XW Claystone. Extremely low strength. Is(50) = 0.01MPa; \* - 15 Some HW Sandstone patches XW Dark brown patches of iron oxide A (15.21m) Is(50) = 0.04MPa; \* D (15.25m)precipitate throughout. HW 100 (33)- Js; 15°-25° (1/m); Joints are irregular, rough, weathered with GP. 15.80m-16.80m: XW Claystone. XW Extremely low strength. Logs JINGI BH Is(50) = 0.10MPa; \* Is(50) = 0.11MPa; \* D (16.76m) 17 100 \_\_ 17.10m-17.30m: XW Claystone. (77) XW Extremely low strength HW - 18 Is(50) = 0.10MPa; \* Is(50) = 0.05MPa; \* D (18.35m) 100 18.55m-18.90m: XW Claystone. XW (45)Extremely low strength - 19 HW Log GLB 19.60m-20.20m: XW Claystone Extremely low strength. XW REMARKS J\_Kk = Kumbarilla Beds LOGGED BY MS \* For this specimen, the load cell used does not comply with the test method requirements.



# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH12
SHEET	_3_ of _3_
REFERENCE No	11846

PRO	JECT	_Jingi_	<u>Jingi Cre</u>	ek Br	idgesite Investigation							
LOC	ATION	Pier 10 - Right Hand Side COORDINATE								ORDINATES <u>287030.2 E; 7024325.</u>	.5 <u>N</u>	
PRO	JECT N	CT No <u>FG6169</u> SURFACE R.L. <u>315.27m</u> PLUNGE DATE STARTED <u>27/6/14</u>								14_ GRID DATUM <u>MGA 94 Zone</u>	<u>e 56</u>	
JOB	No	222/1	8C/5		HEIGHT DATUM <u>AHD</u> BEARING _			DATE COM	IPLETED 2	7/6/1	DRILLER North Coast [	Drilling _
(m)	R.L. (m)	R IG BORING DRILLING	RQD ()%		MATERIAL	\.	2	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA	
DEPTH (m)		ER NG EDR		PLE	DESCRIPTION	LITHOLOGY				띪	AND	SAMPLES
20	295.27	AÚGI CASI WAS COR	CORE REC %	SAMPLE		Ē	USC	#¥±×¬	UO W>O∑≷} U	GRA	TEST RESULTS	SAMPLI
	295.07		100		CLAYSTONE (J_Kk)		ΧV				Is(50) = 0.02MPa: *	D (20.15m)
-					HW: (Cont'd)	_			- : : : : : :		Is(50) = 0.01MPa; *	A (20.19m)
-					Borehole terminated at 20.2m				-::::::::::::::::::::::::::::::::::::::			-
-21												-
Ė												
-								: : : : : : <del>-</del>				-
Ė												
-22												-
Ė												-
-								: : : : : : : : : : : : : : : : : : :	-::::::::::::::::::::::::::::::::::::::			-
Ė												
-23												-
-												-
.F												-
-												:
24												-
												:
												-
5-												:
25												-
-												-
												-
26												-
												-
27												-
								=======================================	= : : : : :			-
												:
28												-
												:
												-
E												
29								-	<u> </u>			-
									- : : : : : :			=
												-
24 25 25 26 26 26 26 26 26 26 26 26 26 26 26 26												
	EMARK	s J Kk	= Kumb	arilla	Beds			<del></del>	<u> </u>		LOGGED BY	
17					n, the load cell used does not comply with the tes	meth	od r	equirements			MS	
							<u> </u>					