

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH C73
SHEET 1 of 2
REFERENCE No H11201

PROJECT Bruce Highway Upgrade (Cooroy to Curra) Section C
LOCATION Embankment 8/Potential Access Overpass Abut A COORDINATES 471985.9 E; 7093831.0 N
PROJECT No FG5799 SURFACE R.L. 71.60m PLUNGE _____ DATE STARTED 19/09/11 GRID DATUM MGA94
JOB No 232/10A/2 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 19/09/11 DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	71.60												
0.1	71.35					TOPSOIL: Grey/brown, dry, gravelly silt.							
0.5					A	Sandy SILT (Fill): Brown/grey, fine grained, moist, very stiff, low plasticity.	(ML)					10,14,13 N=27	SPT
1.5	69.85					Sandy CLAY (Alluvium): Grey mottled with red iron staining, moist, stiff to very stiff.							
2.5					B	Intermediate to high plasticity, sand fraction is fine grained.	(CI-CH)					6,7,7 N=14	SPT
3.5													
4.5					C							6,7,10 N=17	SPT
5.5													
6.5	66.10				D	SANDSTONE (HW): Brown/grey, fine grained.	HW					30/100 N>50	SPT
7.5	64.50				E							30/50 N>50	SPT
8.5			(0)			SANDSTONE (MW): Brown/grey, fine grained, generally massive, medium strength, indurated and/or slightly metamorphosed. Defects: -Joint at 35° (3-4/m) -Joint at 45°-50° (3-4/m) -Joint at 70° (2-3/m) Defects are mainly closely spaced. Defect surfaces are planar, tight, slightly rough, thinly clay infilled, iron stained. Occasional siltstone interbeds. Bedding dips at 50°.	MW				J, 50°, Pl, T, S, Clnf J, 50°, Pl, T, S, FeSt HW Clayey Seam Clay Seam, 50° Siltstone interbed J, 30°, L, R, FeSt		
9.5	62.89		100 (6)			SANDSTONE (SW): Grey, fine grained, generally massive, mainly high strength, indurated and/or slightly metamorphosed. (See over)	SW					Is(50) = 0.56MPa Is(50) = 0.39MPa J, 70°, Pl, T, S, Clnf, FeSt J, 50°, Pl, T, S, FeSt J, 40°, Pl, O, SR, FeSts(50) = 3.48MPa J, 40°, Pl, O, R, FeSt	x o x o
10			100 (23)										

REMARKS _____

LOGGED BY
JA/DC

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH C73
SHEET 2 of 2
REFERENCE No H11201

PROJECT Bruce Highway Upgrade (Cooroy to Curra) Section C
LOCATION Embankment 8/Potential Access Overpass Abut A COORDINATES 471985.9 E; 7093831.0 N
PROJECT No FG5799 SURFACE R.L. 71.60m PLUNGE DATE STARTED 19/09/11 GRID DATUM MGA94
JOB No 232/10A/2 HEIGHT DATUM AHD BEARING DATE COMPLETED 19/09/11 DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS				
										EH VH H M L VL EL	20 50 100 200 500 1000 2000							
10	61.60					SANDSTONE (SW): Cont'd Defects: -Joint at 10° (3/m) -Joint at 40°-50° (2/m) -Joint at 60° (1/m) -Joint at 80° (1/m) Defect spacing is close to medium. Defect surfaces are planar, open , slightly rough, iron stained or clay infilled. Occasional siltstone interbeds dipping at 40°-50°. 12.92-13.67: Interbedded sandstone/siltstone. Bedding dips approximately 40°.	SW			J, 70°, Pl, O, S, FeSt	<div>J, 10°, Pl, O, S, FeSt Is(50) = 2.38MPa</div> <div>J, 80°, Pl, T, S, FeSt Is(50) = 2.23MPa</div> <div>Siltstone interbed, 50°</div> <div>J, 70°, Pl, T, Clnf</div> <div>J, 70°, Pl, T, S, Cn</div> <div>Is(50) = 2.47MPa</div> <div>CLy BZ</div> <div>J, 70°, Pl, O, S, Clnf</div> <div>CLy BZ</div> <div>J, 70°, Pl, T, S, Cn</div> <div>Is(50) = 0.44MPa</div>	x o						
11			100 (0)															
12			100 (35)															x
13	57.93		100															x
14						Borehole terminated at 13.67m												
15																		
16																		
17																		
18																		
19																		
20																		

REMARKS

LOGGED BY
JA/DC



CORE PHOTO LOG - BH C73

Project Name:	BRUCE HIGHWAY UPGRADE - SECTION C		
Project No.:	FG5799	Date:	20/09/2011
Details:	Structure	Start Depth (m):	7.10
Reference No.:	H11201	Finish Depth (m):	13.67



SCALE 1:5