COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



TMR.GLB Log A_ENGINEERING BOREHOLE LOG W LITHOLOGY JINGI JINGI BH LOGS.GPJ <<DrawingFile>> Datgel CPT Tool glint Add-In 18/12/2014 13:31

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH08
SHEET	_1_ of _2_
REFERENCE No	11842

PRO.	JECT	_ <u>J</u> i	ngi .	Jingi Cree	k Br	idgesite Investigation						
LOC	NOITA	<u>P</u>	<u>er 6</u>	- Right I	land	Side				СО	ORDINATES <u>287062.8 E; 7024302.</u>	<u> 6 N</u>
PRO.	JECT N	0 <u>F</u>	<u> 361</u>	69		SURFACE R.L. <u>315.39m</u> PLUNGE			DATE STARTED 13	3/7/	14 GRID DATUM <u>MGA 94 Zone</u>	<u> 56</u>
JOB	No	_2	22/1	8C/5		HEIGHT DATUM <u>AHD</u> BEARING _			DATE COMPLETED 14	<u>1/7/</u>	14 DRILLER North Coast [<u> Drilling</u>
O DEPTH (m)	R.L. (m)		WASH BORING CORE DRILLING		SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	INTACT DEFECT STRENGTH SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
-	314.99					Silty CLAY (TOPSOIL) Dark grey black, moist, soft. Medium to low plasticity. Some sand, gravel and organic matter.		(CI- CH				-
- - - - 1 - - - - -					А	Silty CLAY (ALLUVIAL) Dark grey, moist, firm to stiff. High plasticity. Trace organic matter.		(CH			1,3,3 N=6	SPT
-2	312.39				В						2,3,6 N=9	SPT -
3.g0 - - - - - -	312.33	-			С	Sandy CLAY (ALLUVIAL) Grey brown, moist, very stiff to hard. Low plasticity. Fine to medium grained sand.		(6)			4,8,12 N=20	SPT -
- 4 - - - - - - - - - - -	310.59				D	4.00m: High content of fine to medium sand.		(CL)		12,16,26 N=42	SPT -
- - - - - - - - - - -					Е	Clayey SAND (ALLUVIAL) Grey brown, moist, mainly dense to very dense. Fine to coarse grained sand. Some gravel.					20,30/140mm	SPT :
-6 - - - - - - - - - - - - - - - - - -					F			(SC			10,16,20 N=36	SPT -
-7 - - - - 7.50	307.89				G				<u> </u>		11,20,17 N=37	SPT]
- 8 	306.49				Н	Sandy Gravelly CLAY Dark brown, red, moist, hard. Low plasticity. Fine to medium gravel.		(CL)		8,19,19 N=38	SPT -
- 9 	230.70				J	CLAYSTONE (J_Kk) XW: Recovered as pale grey, moist, hard, silty clay. Low plasticity.		xw	, +		14,24,30/100mm	SPT -
REMARKS J_Kk = Kumbarilla Beds * For this specimen, the load cell used does not comply with the test method requirements. LOGGED BY MS								od re	equirements.		•	



TMR.GLB Log A_ENGINEERING BOREHOLE LOG W LITHOLOGY JINGI JINGI BH LOGS.GPJ <<DrawingFile>> Datgel CPT Tool glint Add-In 18/12/2014 13:31

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH08
SHEET	_2_ of _2_
REFERENCE No	11842

	JECT				idgesite Investigation						
	CATION Pier 6 - Right Hand Side OJECT No FG6169 SURFACE R.L315.39m PLUNGE D										
JOB	NO	_2221	160/5		HEIGHT DATUM <u>AHD</u> BEARING			DATE COMPLETED 14	1///	14_ DRILLER NOTTI COAST D	rillirig _
(m)	R.L. (m)	NG NG HBORING DRILLING	RQD ()%		MATERIAL	γ.	ING	INTACT DEFECT STRENGTH SPACING (mm)	LOG	ADDITIONAL DATA	
DEPTH (m)		E BO		빌	DESCRIPTION	OLOG	뛺		HC HC	AND	PLES S
出 10	305.39	AUGE CASII WASH	CORE REC %	SAMPLE		ГІТНОГОВУ	USC WEA	STRENGTH SPACING (mm)	GRAPHIC LOG	TEST RESULTS	SAMPLES
				K	CLAYSTONE (J_Kk) XW: (Cont'd)					24,30/140mm	SPT]
- - -											-
11 - - - -				L	Becoming pale grey cream with some gravel sized HW rock fragments.					26,30/125mm	SPT :
- - -							XW				-
12 - - -				M						30/140mm	SPT -
-											-
- 13 13.20	302.19		(400)	N						30/120mm	SPT _
			(100)		CLAYSTONE (J_Kk) HW: Pale grey, yellow, white, with dark						
-					brown patches, fine grained, thickly bedded, very low to low strength.					U00 0401 B	-
- 14			100		Some zones of XW rock.		HW			UCS=918kPa	UCS -
-			(83)		Dark brown patches of iron oxide precipitate.					Is(50) = 0.13MPa; * Is(50) = 0.07MPa; *	D (14.14m)
										1S(50) = 0.07 MPa,	A (14.18m)
-							XW				=
_ 15											_
-											-
			100								3
-			(100)								=
_ 16							HW]
-										Is(50) = 0.11MPa; * Is(50) = 0.05MPa; *	D (16.16m)
										is(50) - 0.05iviFa,	A (16.20m)
-											-
_ _ 17			100]
-			(43)				XW			17.15m-17.40m: XW Claystone.	-
							7,11			Extremely low strength.	_
- - - - 18							HW			Is(50) = 0.02MPa; * Is(50) = 0.04MPa; *	A _(17.70m) D _(17.75m)
- '0 - -							XW			18.05m-18.60m: XW Claystone. Extremely low strength.	-
=			100 (66)						-		-
-			(00)				HW				-
- 19 - 19.20	296.19		100				XW			19.10m-19.20m: XW Claystone. Extremely low	D.,,,,,,,
-					Borehole terminated at 19.2m					strength. Is(50) = 0.04MPa; *	A (19.20m)
-											-
20											=
	REMARK		<u>= Kumba</u>							LOGGED BY	
		* For	this spec	cimer	n, the load cell used does not comply with the test	<u>neth</u>	od re	quirements.		MS	