

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>





# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No   BH01    
 SHEET   2   of   7    
 REFERENCE No           

PROJECT   BURDEKIN REALIGNMENT BRIDGE PRELIMINARY FOUNDATION INVESTIGATION - CONCEPT / PLANNING STAGE    
 LOCATION   Abutment A @ CH 104400   COORDINATES   541320.0 E; 7827651.3 N    
 PROJECT No   FG5945   SURFACE R.L.   14.65m   PLUNGE            DATE STARTED   3/9/11   GRID DATUM   PMBH    
 JOB No   5/10L/951   HEIGHT DATUM   AHD   BEARING            DATE COMPLETED   4/9/11   DRILLER   R&D Drilling Pty Ltd  

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH					DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
									EH	VH	VI	VI	VI				
10	4.65				G	<b>Clayey Sandy SILT (ALLUVIAL)</b> Brown yellow to grey, moist, firm to very stiff.  Mainly low to medium plasticity.										4,6,10 N=16	SPT
11																	
12					H	soft clay layer at 11.5m										2,2,3 N=5	SPT
13							(ML)										
14					J											2,3,5 N=8	SPT
15					K											4,6,8 N=14	SPT
16	-0.87				L	<b>Silty SAND (ALLUVIAL)</b> Brown to yellow, moist, medium dense.  Fine to coarse grained sand; some gravel.										9,9,10 N=19	SPT
17							(SM)										
18					M											9,12,13 N=25	SPT
19	-3.85				N	<b>Gravelly SAND (ALLUVIAL)</b> Brown to yellow, moist, medium dense to dense.  Fine to coarse grained sand; fine to medium grained gravel.										15,28,25 N>50	SPT
20	-5.35																

REMARKS \_\_\_\_\_

LOGGED BY  
BW / MS







# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No	<u>BH01</u>
SHEET	<u>5</u> of <u>7</u>
REFERENCE No	-----

PROJECT BURDEKIN REALIGNMENT BRIDGE PRELIMINARY FOUNDATION INVESTIGATION - CONCEPT / PLANNING STAGE  
 LOCATION Abutment A @ CH 104400 COORDINATES 541320.0 E; 7827651.3 N  
 PROJECT No FG5945 SURFACE R.L. 14.65m PLUNGE \_\_\_\_\_ DATE STARTED 3/9/11 GRID DATUM PMBH  
 JOB No 5/10L/951 HEIGHT DATUM AHD BEARING \_\_\_\_\_ DATE COMPLETED 4/9/11 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH						DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
									EH	VH	IM	JL	VL	EL				
40	-25.35				AC	<b>Silty SAND (ALLUVIAL)</b> (Cont'd)										Based on Driller's logs only	12,15,11 N=26	SPT
41							(SM)											
42	-27.35				AD	Becoming clayey sand at 41.5m.											12,22,17 N=39	SPT
43					AE	<b>GRANODIORITE</b> <b>Intrusive, crystalline, medium to coarse grained, acid to basic igneous rock</b> <b>XW:</b> Generally exhibits the engineering properties of dark brown to dark grey, moist, hard sandy silt.											14,26,30/130mm N>50	SPT
44					AF	Low plasticity.											30/130mm, HB N>50	SPT
45	-29.85		(93)			<b>HW:</b> Dark grey to pale brown patches, fine to medium grained, massive, very low to low strength.  Defects: - Joints @ 30° (1/m) - Joint @ 65° (1/m)  Defects are generally medium wide spaced, planar, rough, open and weathered.  Several bands of HW-XW fine to medium grained microdiorite.										DD = 2.18t/m <sup>3</sup> ; WD = 2.36t/m <sup>3</sup> ; MC = 7.8%; SOIL UCS=472kPa		
46			100	(0)														
47			100	(0)			HW											XW-HW white granite band
48																		
49			100	(60)														XW granite band
50	-35.35																Is(50) = 0.12MPa Is(50) = 0.17MPa	x o

REMARKS \_\_\_\_\_

LOGGED BY  
BW / MS





# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No	BH01
SHEET	7 of 7
REFERENCE No	

PROJECT BURDEKIN REALIGNMENT BRIDGE PRELIMINARY FOUNDATION INVESTIGATION - CONCEPT / PLANNING STAGE  
 LOCATION Abutment A @ CH 104400 COORDINATES 541320.0 E; 7827651.3 N  
 PROJECT No FG5945 SURFACE R.L. 14.65m PLUNGE \_\_\_\_\_ DATE STARTED 3/9/11 GRID DATUM PMBH  
 JOB No 5/10L/951 HEIGHT DATUM AHD BEARING \_\_\_\_\_ DATE COMPLETED 4/9/11 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH					DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
							EH	VH	TM	JL	EL				
60	-45.35			<b>GRANITE</b> MW: (Cont'd) Defects: - Joints @ 20-30° (2/m) - Joints @ 75-80 (2/m)											
61			100 (55)	Defects are generally close to widely spaced, planar, rough, open and stained.	MW								Is(50) = 0.83MPa Is(50) = 0.78MPa	o x	
62	-46.85			60.55-61.5: MW Hornblende Diorite band - black, fine grained, massive, medium strength rock band. <b>SW:</b> White pink and grey, medium to coarse grained, massive, very high strength to occasionally extremely high strength. Defects: - Joints @ 25-30° (4/m) - Joints @ 55-65° (1/m)									Is(50) = 5.48MPa Is(50) = 9.45MPa Is(50) = 6.94MPa	o x o	
63				Defects are generally medium to very widely spaced, planar, rough, open and iron stained.									UCS=60.4MPa Is(50) = 8.89MPa Is(50) = 8.51MPa	x o	
64			100 (100)		SW								Is(50) = 6.64MPa Is(50) = 7.79MPa	x o	
65													Is(50) = 10.11MPa Is(50) = 7.06MPa	x o	
67	-52.35		100	Borehole terminated at 67m											
68															
69															
70															

REMARKS \_\_\_\_\_

LOGGED BY  
BW / MS

<b>Project Name</b>	<b>Burdekin River Bridge Realignment</b>		
<b>Project No</b>	FG 5945	<b>Date</b>	05/09/11
<b>Borehole No</b>	BH 1	<b>TMR H No</b>	
<b>Location</b>	Abutment A	<b>Start Depth (m)</b>	44.50
<b>Detail</b>		<b>Finish Depth (m)</b>	67.00
<b>Chainage</b>		<b>Submitted By</b>	BW
<b>Remarks</b>			



<b>Project Name</b>	<b>Burdekin River Bridge Realignment</b>		
<b>Project No</b>	FG 5945	<b>Date</b>	05/09/11
<b>Borehole No</b>	BH 1	<b>TMR H No</b>	
<b>Location</b>	Abutment A	<b>Start Depth (m)</b>	44.50
<b>Detail</b>		<b>Finish Depth (m)</b>	67.00
<b>Chainage</b>		<b>Submitted By</b>	BW
<b>Remarks</b>			



<b>Project Name</b>	<b>Burdekin River Bridge Realignment</b>		
<b>Project No</b>	FG 5945	<b>Date</b>	05/09/11
<b>Borehole No</b>	BH 1	<b>TMR H No</b>	
<b>Location</b>	Abutment A	<b>Start Depth (m)</b>	44.50
<b>Detail</b>		<b>Finish Depth (m)</b>	67.00
<b>Chainage</b>		<b>Submitted By</b>	BW
<b>Remarks</b>			



SCALE 1:5