

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No BH6
SHEET 1 of 2
REFERENCE No H9786

PROJECT Caboolture River Bridge Foundation Investigation
LOCATION Pier 5 - 14.1m left (along skew) of existing northbound bridge C/L COORDINATES 497552.7 E; 7003538.1 N
PROJECT No FG5439 SURFACE R.L. 4.57 DATE STARTED 09/11/05 DATUM MGA94 Zone 56
JOB No 25/10A/60C DATUM AHD DATE COMPLETED 09/11/05 DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	AUGER Casing WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	4.57					Clayey SAND (Alluvium): Brown, moist, loose, fine to medium grained, some low plasticity fines, some organic matter.						
1												2,3,3 N=6 SPT
2							SC					
3												4,4,5 N=9 SPT
4						Grey-brown and more medium plasticity clay fines below 3.5m. Some dark orange-brown ironstained lenses and some organic matter throughout.						2,3,3 N=6 SPT
5	-0.43					SAND (Alluvium): Brown, moist, loose to medium dense, coarse grained, occasional high plasticity grey clay bands, trace of fine gravel up to 5mm.	SP				5.0m: Water loss	2,4,6 N=10 SPT
6	-1.93											
7						Gravelly SAND (Alluvium): Pale brown, moist, loose, coarse grained, fine gravel up to 6mm.	SP					4,3,4 N=7 SPT
8	-3.83											
9						SANDSTONE: HW: Orange-brown, ironstained, medium grained, very low strength, subhorizontal bedding laminations visible.	HW					30/110,-- N>50 SPT
10	-5.43											

REMARKS

LOGGED BY
A O'Rourke



Queensland
Government

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No BH6

SHEET 2 of 2

REFERENCE No H9786

PROJECT Caboolture River Bridge Foundation Investigation

LOCATION Pier 5 - 14.1m left (along skew) of existing northbound bridge C/L

COORDINATES 497552.7 E; 7003538.1 N

PROJECT No FG5439

SURFACE R.L. 4.57

DATE STARTED 09/11/05

DATUM MGA94 Zone 56

JOB No 25/10A/60C

DATUM AHD

DATE COMPLETED 09/11/05

DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
10	-5.43												
	-5.53					SANDSTONE: HW: As above.	HW				<i>Pile Tip -5.5</i>	N>50	SPT
			(88)			MW: Orange-brown, ironstained, a few light grey (non-ironstained) bands, medium grained, low to high strength, occasional coarse grained bands, thin dark brown subhorizontal carbonaceous laminae and black coal laminae, occasional bands containing grey-brown siltstone rip-up clasts.					Is(50)=0.06 MPa Is(50)=0.38 MPa	x	
11													
						Defects: Numerous subhorizontal bedding partings and low angle joints. Rare 50-60° irregular joints.	MW				11-11.28m: Iron cemented band. Is(50)=1.06 MPa Is(50)=1.19 MPa	x	
12													
13	-8.53		100			SW: Light grey, medium to coarse grained, medium to high strength, occasional black coal laminae and bands up to 30mm thick, fairly massive.					12.58-13.10m: Numerous moderate to high angle drilling induced fractures. Is(50)=0.39 MPa Is(50)=0.51 MPa	x	
			(91)			Defects: Occasional subhorizontal bedding partings. Rare 60-70° irregular joints.	SW						
14													
15													
16	-11.53		100			Borehole terminated at 16.1m					15.56-15.90m: Numerous moderate to high angle drilling induced fractures.		
17													
18													
19													
20													

REMARKS

LOGGED BY
A O'Rourke

Project: FOUNDATION INVESTIGATION FOR THE WIDENING OF THE CAPTAIN WHISH BRIDGES (NORTH AND SOUTHBOUND) – CABOOLTURE RIVER


Borehole No: BH6 Pier 5

Start Depth: 10.10m

Finish Depth: 16.10m

Project No: FG5439

H No: 9786



SCALE 1:5

F:GEOT043/1



Point Load Strength Index - Test Report

Project: CABOOLTURE RIVER BRIDGE

Project No: FG 5439

Date Sampled 9/11/05

Feature: PIER 5

Sample Type: NMLC ROCK CORE

Date Tested 6/12/05

Report No. FG 5439/1/GS05/801/AS4133.4.1

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS05/801-A	BH6	10.30	D	0.06	0.06	VL	Sandstone
GS05/801-B	BH6	10.33	A	0.42	0.38	M	Sandstone
GS05/801-C	BH6	11.15	D	1.07	1.06	H	Sandstone
GS05/801-D	BH6	11.18	A	1.38	1.19	H	Sandstone
GS05/801-E	BH6	13.18	D	0.39	0.39	M	Sandstone
GS05/801-F	BH6	13.21	A	0.57	0.51	M	Sandstone

Sample Remarks

* D - Diametral; A - Axial; B - Block; I - Irregular;

** EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High (taken from AS1726 Table 8A)

Remarks / Variations to Test Procedures:

Test Method: AS4133.4.1

Software Version 2.03 April 2005

Client Name: RS&E STRUCTURES DIVISION

Client Address: PO BOX 1412 SPRING HILL 4001

Signatory

(Peter Reynolds)



Accreditation Number: 2302
Accredited for compliance
with ISO/IEC 17025

This document is issued in
accordance with NATA's
accreditation requirements.