## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

## MAIN ROADS DEPARTMENT

DR	IL	LIN	G	R	E	P	0	R	I
----	----	-----	---	---	---	---	---	---	---

PROJECT WOOLLOONGABBA INTERCHANGE	PROJECT No1/21
DISTRICT NO	HOLE No 3
ROAD. REDFERN STREET	JOB No
LOCATION 104' east of eastern alignment	RL DATUM B.C.C.
Ipswich Road and 8' north from southern alignment Redfern Street TYPE AND SIZE OF DRILLING .0-26.0, 2" hollow auger, 26.0-34.0 AXM Diamond	COLLAR

_	DEPTH			SAMPLE				
	1"=5 t REC.		DIAGRAM		STRATA	DESCRIPTION OF SOIL ROCK		TYPE
- - - -	2.5			2.5	PAVEMENT	mainly quartz gravel		
 	5.0				CLAY	2.5-5.3 pink and white mottled, plastic,	10	עט
	6.3				OTAY	moist, firm. 5.3-8.0 dark grey brown mottled, moist,	20	UD
	7.5 8.8			8.0		firm, some sandy clay bands	3C	UD
- - - -	10.0					2 0 16 0 danta	4C	UD
= -	12.5				CLAYEY	8.0-16.0 dark grey brown grading to grey pebbly	5 <b>0</b>	UD
=-	15.0 15.5				SAND	16.0-22.7 yellow ironstained pebbly grading to gravel	<u>60</u>	UD
	17.5 17.8					8.0-12.0 moist 12.0-22.7 saturated	70	עט
Ē	20.0					12.0-22.7 Saturated	30	מט
	22.5			22.7			90	מט
	42.8				DECOMPOSED CONGLOMERATE	ironstained, pebbly	- 100	525.
	26.0	- 00		26.0				
	27.0	12		29.2	HIGHLY VEATHERED CONGLOMERATE	ironstained, crumbly		
= = = = = =	30.0	75		34.0	SLIGHTLY VEATHERED CONGLOMERATE	blue grey, pebbles 0.25-1.0 inch, hard tough - two 1 inch clay bands in bottom foot		
_	3-4.0			37.00		End of Hole		

DRILLER C:W. J.P.	PLANTMRD.GEMCO.9310
REMARKS	
DATE 11/4/66 GEOLOGIST	APPROVED Stallipurey DATE 17/6/66.
(c) State of Queensland (Department of Transport and Main Roads) 2020, CC B	Y 4.0. Please note copyright and limitation of liability notices on attached cover page