COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/6-2010

PROJECT		a <u>v</u> Ļ	Jpgrade (Cooroy to Curra) Section C						· 	
LOCATION	Cut 16 COORDINATES 470403.4 E; 7097742.7 N FG5799 SURFACE R.L. 69.40m PLUNGE DATE STARTED 15/08/11 GRID DATUM MGA94						<u>7 N</u>			
			SURFACE R.L69.40m PLUNGE _							
JOB No	_232/10A/2		HEIGHT DATUM <u>AHD</u> BEARING			DATE COM	MPLETED _	<u>15/08</u>	DRILLER Drillsure Pty	<u></u>
DEPTH (m)	AVGER CASING WAS	SAMPLE	MATERIAL DESCRIPTION	гітногосу	SC EATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES
		Ś	TOPSOIL - Dale grove describ	╬	S ≥		11111	20		AS ⊨
69.20			TOPSOIL: Pale grey, dry, silt. SILTSTONE (XW): Generally exhibits engineering properties of a brown/grey, fine grained, dry, very dense, silty gravel.	× × × × × × × × × × × × × × × × × × ×	9	-			- Based on driller's logs only	
<u> </u>	4	Α		X X	XW]	-		12,30,30/100	
E				IX X		-			N>50	-
67.50	(24)			× × × × ×						
UPGRADE.SECTION C.GPJ. DWG-46555.GDW. Detgel CPT Trol glint Add-In 12/12/2011 16:30	(31)		SANDSTONE (MW): Grey/brown, fine to medium grained, bedded, generally medium to mainly high strength, indurated and/or slightly						J. Subvertical, I, T, R, CInf	-
Add-In 12	(27)		metamorphosed. Contains prominent thin siltstone interbeds throughout. Bedding dips at 40°.						Is(50) = 0.31MPa Is(50) = 1.42MPa	x -
Trool gilvit			Defects:						J, Subvertical, I, T BP, 40°, PI, T, SR J, 30°, PI, T, CInf	-
Datgel CP1			-Bedding parting at 40° (~8/m) -Joint at 30° (<1/m) -Joint at 45° (1-2/m)						ls(50) = 1.61MPa ls(50) = 1.93MPa	x -
352.GDW	100		-Joint at 70° (<1/m) -Joint at subvertical (1/m)		!				l — J, 70°, Pl, T, Cinf	-
PJ DWG46	(0)		Defect spacing is close to medium. Defect surfaces are planar, tight, slightly rough, clay infilled, iron stained.						– J, Subvertical, I, T, CInf	
0.0NOITO									√ J, 50°, PI, T BP, 40°, O, SR, Cn]
BRADE SE										
	(41)] =
OLD OMR LIB ON A.B. NORNEERING BOREHOLE LOG WLITHOLOGY F65799 - BRUCE HWY					MW		_		ls(50) = 1.06MPa ls(50) = 4.56MPa	x -
-62599-					i		<u> </u>	ш	⊒ BZ	:
LLOGY							+	-	─ Clay Seam	
위 <u>-</u> 7	100			:::					DD 0 5000 3 MO 4 100	
1901	(45)								DD = 2.58t/m ³ ; MC = 1.1%; UCS=10.25MPa	UCS -
OREHOL 1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-										
SINCE 8 8										-
NGINEE							<u> </u>			
8 A E	100	\dashv					4		Is(50) = 0.66MPa	×
9 9				: : :					CLy Zone IS(50) = 0.36WI a IS(50) = 1.38MPa IS(50) = 1.38MPa	0 1
1 1 1							_		, 10 ; 1 ; 0; 10; Ollin; 1 000	
OMR.							=		Sandy Clay Zone	
				: : :						
REMARKS	*Point load failed	<u>alo</u>	ng existing defect	0.00					LOGGED BY	
								- -	JA/DC	



ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/6-2010


BOREHOLE No	BH C61				
SHEET	_2_ of _2_				
REFERENCE No	<u>H11143</u>				

PRO	JEÇT	경에 50 개인 20 개인										
PRO	JECT No									DATUM MGA94		
JOB	No	232/	10 <u>A</u> /2		HEIGHT DATUM _AHD BEARING _			DATE COMPLETED	15/08	<u>8/11</u> [DRILLER <u>Drillsure Pty L</u>	<u>.td</u>
DEPTH (m)	R.L. (m) 59.40	AÚGER CASING WASH BORING CORE DRILLING	RQD ()% CORE REC%	SAMPLE	MATERIAL DESCRIPTION	ПТНОГОСУ	USC	INTACT DEFECT STRENGTH SPACING (mm)	GRAPHIC LOG		OITIONAL DATA AND ST RESULTS	SAMPLES TESTS
-11			100 (0)		SANDSTONE (MW): Cont'd 11.0m-11.6m: Becomming coarse grained conglomerate.		MW			H	FeSt Is(50) = 0.08MPa; * Is(50) = 0.76MPa Is(50) = 0.84MPa Is(50) = 0.49MPa	X -
- 13	56.25		100_		Borehole terminated at 13.15m					BZ J, Subvertica		-
14 15 16 17 17 18 19 19 19 19 19 19 19 19 19 19 19 19 19				- A Company of the Co				*				
20	REMARKS *Point load failed along existing defect.							LOGGED BY				
INCHIPANAO A TIME TO THE TIME							JA/DC					



CORE PHOTO LOG - BH C61

Project Name:	BRUCE HIGHWAY UPGRADE - SECTION C						
Project No.:	FG5799	Date:	08/09/2011				
Details:	Cut 16	Start Depth (m):	1.90				
Reference No.:	H11143	Finish Depth (m):	13.15				





CORE PHOTO LOG - BH C61

Project Name:	BRUCE HIGHWAY UPGRADE - SECTION C					
Project No.:	FG5799	Date:	08/09/2011			
Details:	Cut 16	Start Depth (m):	1.90			
Reference No.:	H11143	Finish Depth (m):	13.15			

