

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH301**
SHEET **1** of **4**
REFERENCE No **11479**

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464703.6 E; 7871500.6 N
PROJECT No FG6020 SURFACE R.L. 12.52m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	12.52												
12.22						Silty CLAY (TOPSOIL) Dark brown, moist, soft to firm. Medium plasticity. Some tree roots.							
A						Silty CLAY Dark brown, grey, moist, very stiff. Medium to high plasticity.	(Cl - CH)					3,7,10 N=17	SPT
B												6,10,13 N=23	SPT
10.52						Sandy SILT Pale grey, pale brown, moist, hard. Low plasticity. Some white calcareous material.						9,18,30 N=48	SPT
C												15,23,30/110mm N>50	SPT
D							(ML)					30,30/90mm,HB N>50	SPT
E												30/140mm,30/100mm,HB N>50	SPT
7.27						Silty SAND Grey, pale brown, pale yellow, moist, very dense. Fine to medium grained sand. Some coarse grains.						14,29,30/90mm N>50	SPT
F												17,30/150mm,30/75mm N>50	SPT
G							(SM)						
H						Minor sandy silt lens. Grey, brown, moist, hard. Low plasticity silt. Very fine grained sand.							
2.52													

REMARKS Standpipe piezometer installed.

LOGGED BY
MS

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH301
SHEET 2 of 4
REFERENCE No 11479

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464703.6 E; 7871500.6 N
PROJECT No FG6020 SURFACE R.L. 12.52m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	2.52												
11					J	Silty SAND (Cont'd) Becoming very fine grained, medium dense sand.						6,9,12 N=21	SPT
12					K	Becoming fine to medium grained, dense sand.	(SM)					8,14,20 N=34	SPT
13	-0.48				L	Clayey SAND Pale grey to pale brown, moist, dense. Fine to coarse grained sand. Some places high clay content.						12,15,23 N=38	SPT
14					M							11,18,24 N=42	SPT
15					N		(SC)					10,13,19 N=32	SPT
16													
17													
18	-4.98				P	Clayey SAND (RESIDUAL) Pale grey to pale brown, white, moist, very dense. Fine to coarse grained sand.						16,26,29 N>50	SPT
19					Q		(SC)					17,24,30/130mm N>50	SPT
20	-7.48					(See over)							

REMARKS Standpipe piezometer installed.

LOGGED BY
MS

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH301
SHEET 3 of 4
REFERENCE No 11479

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464703.6 E; 7871500.6 N
PROJECT No FG6020 SURFACE R.L. 12.52m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-7.48		CORE REC %									
21				R	Clayey SAND (RESIDUAL) (Cont'd)		(SC)				21,23,30/110mm N>50	SPT
22	-9.48			S	TUFF Fine to medium grained, pyroclastic rock. XW: Generally exhibits the engineering properties of grey brown white, moist, hard sandy silt. Low plasticity.						8,23,23 N=46	SPT
23				T			XW				21,28,50/95mm N>50	SPT
24					Some XW - HW rock fragments.							
25	-12.58			U							30/100mm N>50	SPT
26			(0) 100 (0)		HW: Pale grey, pale brown to white, fine grained, massive - fractured, very low to low strength. Defects: - Joints @ 35° (1/m) - Joints @ 40°-50° (3/m) - Joints @ 60°-70° (2/m) - Irregular joints (5/m)		HW				Is(50) = 0.03MPa	o
27	-14.63		(0) 100 (0)		Defect surfaces are generally planar or irregular, rough, open, weathered, clayey coated.							
28			(0) 100 (0)		VOLCANIC BRECCIA Pyroclastic rock consisting of angular fragments embedded in a finer grained matrix. MW: Pink brown, grey, fine to coarse grained, massive to fractured, medium to mainly high strength. Occasional very high strength patches. Coarse grained phenocrysts.						UCS=10.5MPa Is(50) = 1.61MPa Is(50) = 2.47MPa	o o
29			(12) 100 (37)		Defects: - Joints @ 45° (5/m) - Joints @ 55° (3/m) - Joints @ 60°-70° (5/m) - Irregular joints (4/m)		MW				Is(50) = 0.96MPa Is(50) = 3.62MPa	o o
30	-17.48		(0) 100		Defects are generally planar or irregular,						Is(50) = 1.46MPa	o
											HW zone, low strength	

REMARKS Standpipe piezometer installed.

LOGGED BY
MS

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH301
SHEET 4 of 4
REFERENCE No 11479

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464703.6 E; 7871500.6 N
PROJECT No FG6020 SURFACE R.L. 12.52m PLUNGE _____ DATE STARTED 20/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/4/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH						DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
									EH	VH	H	M	L	VL	EL			
30	-17.48					rough, open, some weathered, clay infilled. VOLCANIC BRECCIA MW: (Cont'd)												
31			100 (7)					MW									Is(50) = 1.00MPa Is(50) = 1.61MPa Is(50) = 0.56MPa	o o o
	-19.38		100 (23)														Is(50) = 1.21MPa	o
32			100			Borehole terminated at 31.9m											HW / MW zone, low to medium strength	
33																		
34																		
35																		
36																		
37																		
38																		
39																		
40																		

REMARKS Standpipe piezometer installed.

LOGGED BY
MS

CORE PHOTO LOG

DEPARTMENT OF TRANSPORT & MAIN ROADS
Geotechnical Section
35 Butterfield Street, HERSTON Qld 4006
Phone 07 3066 3336



Department of
Transport and Main Roads

