COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



: PIER 6 -38185E 47659N

PROJECT

LOCATION

ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F873 NOV/87

PEDESTRIAN OVERPASS OVER GATEWAY ARTERIAL AT DEAGON

BOREHOLE No : 3

SHEET : 1

: 1 OF 2

REFERENCE No : H7165

PROJE	CT No				SURFACE R.L.: 5.47	••••		DF	ILLE	DALY BROS	
EPTH (m)	₹.L. (m)	AUGER CORE DRILLING CORE OFFICE OTHER	RQD ()%	CORE LOSS	MATERIAL DESCRIPTION CLAY	П	INTACT STRENGTH	DEFECT	GRAPHIC LOG	 ADDITIONAL DATA AND TEST RESULTS	SAMPLES
-1	3.97				Grey, with some brown mottling, firm, moist alluvium. medium to high plasticity. sand content and plant roots throughout.	СН				ĹL=47.6% PI=28.4%	U48
-3					BASALT GREY, FINE GRAINED, MASSIVE, VOLCANIC ROCK. Grey-green becoming brown with depth, with engineering propeties of a dense clayey sand. Rock structure clearly visible.	XW				N=17 N≃36	SPT
: :	0.67				grey to black, with high strength rock kernels in part.	ни				 N=40/130*	SPT
		The second secon	97		Grey,open defects generally low to medium angle, clay coatings on defect planes. core also contains many semi-closed brown stained defects.	MW	William I control of the control of				
-9	3.03	A CHARLES AND A CONTROL OF THE CONTR	90	***	CLAY Red to brown, very stiff, moist, residual stratum. medium to high plasticity.	сн					
	4.53							- : : : :		LOGGED BY	



ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F873 NOV/87

BOREHOLE No : 3

SHEET :

: 2 OF 2

REFERENCE No : H7165

PROJECT	:	PEDESTRIAN OVERPASS OVER GATEWAY ARTERIAL AT DEAGON
LOCATION	:	PIER 6 -38185E 47659N

 PROJECT No : 1-694
 SURFACE R.L. : 5.47
 DRILLER : DALY BROS

 JOB No : 140/U13c/41
 DATUM : AHD
 DATE DRILLED : 26/2/93

						•••••		***	2012/73	•••••
(m) HLd30 10-4.53	AUGER CORE DRILLING CASING OTHER XCORE DRILLING CASING OTHER XCORE XCORE CASING OTHER XCORE CASING OTHER XCORE CASING OTHER XCORE CASING OTHER XCORE CASING OTHER XCORE CASING OTHER XCORE CASING OTHER XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCORE XCOR	CORE LOSS	MATERIAL DESCRIPTION	usc		INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
-11	1		CLAY Description as before	c					N=14	SPT
-12 -13 -7.93			BASALT Grey to brown, with engineering propeties of a dense clayey sand rock structure visible.	X	w				N=21 N=60/250	SPT
-14 -15 -16 -17 -18 -19			END OF HOLE							

REMARKS

LOGGED BY

(c) State of Queensland (Department of Transport and Main-Roads) 2020, GC BY 4.0. Please note copyright and limitation of liability no

