

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) *State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by Jacobs*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://ggd.org.au/>

This log has been contributed to the Queensland Geotechnical Database with the permission of Jacobs.

CLIENT : TRANSPORT AND MAIN ROADS

POSITION : E: 349339, N: 8067271 (56 MGA94)

PAGE : 1 OF 1

PROJECT : TNRP

SURFACE ELEVATION : 752.4 (AHD)

DATE DRILLED : 23/10/12 to 23/10/12

JOB NO : CB27000.F672

DIP / AZIMUTH : 90°

LOGGED BY : AJ

LOCATION : MILLAA MILLAA - MILANDA ROAD (641)

CONTRACTOR : N/A

CHECKED BY :

[illegible]

DRILLING				SAMPLES & FIELD TESTS				DENSITY (SPT N-value)				CONSISTENCY (Su) {SPT N-value}					
HA	Hand Auger	RR	Rock Rolling	DS	Disturbed Sample	SPT Standard Penetration Test			VL	Very Loose	0 - 4	VS	Very Soft	< 12 kPa	{0-2}		
AS	Auger Screw	AT	Air Track	ES	Env Soil Sample	U Undisturbed Tube Sample			L	Loose	4 - 10	S	Soft	12 - 25	{2-4}		
AD/T	Auger Drill TC-bit	HQ	HQ Coring	EW	Env Water Sample	W Water Sample			MD	Medium Dense	10 - 30	F	Firm	25 - 50	{4-8}		
AD/V	Auger Drill V-bit	PQ	PQ Coring						D	Dense	30 - 50	St	Stiff	50 - 100	{8-15}		
WB	Washbore	NMLC	NMLC Coring	HP	Hand Penetrometer	MOISTURE CONDITION			VD	Very Dense	50 - 100	VSt	Very Stiff	100 - 200	{15-30}		
				HV	Hand Vane Shear	D = Dry M = Moist W = Wet			CO	Compact	>50/150mm	H	Hard	> 200 kPa	{>30}		
				(P: Peak Su R: Residual Su)													
				N	SPT blows per 300mm												
				HW	SPT penetration by hammer weight												
				RW	SPT penetration by rod weight												
DRILLING PENETRATION																	
VE	Very Easy	F	Firm	VH	Very Hard												
E	Easy	H	Hard														
GROUNDWATER SYMBOLS																	
▼ = Water level (static)																	
▽ = Water level (during drilling)																	