

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://ggd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH C39**
SHEET **1** of **3**
REFERENCE No **H11048**

PROJECT **Bruce Highway Upgrade (Cooroy to Curra) Section C**
LOCATION **Cut 10/Woondum Rd Overpass Pier 2** COORDINATES **471594.1 E: 7094777.5 N**
PROJECT No **FG5799** SURFACE R.L. **79.20m** PLUNGE **-90°** DATE STARTED **25/6/11** GRID DATUM **MGA94**
JOB No **232/10A/2** HEIGHT DATUM **AHD** BEARING DATE COMPLETED **26/6/11** DRILLER **Drillsure Pty Ltd**

DEPTH (m)	R.L. (m)	AUGER Casing WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	79.20											
0	79.10					TOPSOIL Silty CLAY (Residual): Grey/brown, moist, organic. High plasticity; gravel fragments up to 10mm.	(CH)					
1	78.20					SANDSTONE (HW): Brown, medium grained.	HW				30/20 N>50	OPT
2	77.70					SANDSTONE (MW): Grey/red, fine to medium grained, massive, medium to high strength, indurated and/or slightly metamorphosed.	MW				J, 20°, Pl, C, Clnf Is(50) = 0.48MPa Is(50) = 1.11MPa	x o
2	77.08		(0)	100		Defects: -Joint at 50° Defect spacing is close. Defect surfaces are planar, tight, clay infilled.	HW				J, 60°, Pl, T, S, Clnf BZ	
3	76.00		(11)	100		DOLERITE (HW): Orange/brown, fine grained, massive, very low to low strength.	HW				XW Clay Seam	
4			(0)	100		Defects: -Joint at 30° (3-4/m) -Joint at 60° (3-4/m) Defect spacing is close to medium. Defect surfaces are planar, close to tight, slightly rough, clay infilled.					J, 75°, Pl, T, SR, Clnf, FeSt J, 70°, Pl, T, SR, Clnf, FeSt J, 10°, Pl, T, S, FeSt	
5			(28)	100		SANDSTONE (SW): Grey, fine to medium grained, massive, high strength, indurated and/or slightly metamorphosed.	SW				DD = 2.63t/m³, MC = 0.9%; UCS=57.2MPa Is(50) = 3.36MPa	UCS o
6			(14)	100		Defects: -Joint at 30°-40° (2/m) -Joint at 70°-80° (2/m) Defect spacing is close to medium. Defect surfaces are planar, tight or open, clay infilled. Occasional pebbles up to 20mm.					J, Subvertical, I, T, SR, CLy J, 55°, Pl, O, Clnf, 20mm	
7	72.75					DOLERITE (MW): Brown, fine grained, massive, medium to high strength, indurated and/or slightly metamorphosed.	MW				Sharp contact, 50° Is(50) = 0.24MPa; * Is(50) = 0.23MPa	x o
8	71.10		(45)	100		Defects: -Joint at 20° (1-2/m) -Joint at 40°-50° (4/m) Defect spacing is close to medium. Defect surfaces are planar, tight or closed, smooth, clay infilled.					Is(50) = 0.92MPa Is(50) = 1.01MPa	x o
9			(0)	100		SANDSTONE (SW): Grey, fine to medium grained, massive, very high strength, indurated and/or slightly metamorphosed.	SW				Brecciated Zone J, 40°, Pl, O, Clnf J, 70°, Pl, O, SR, FeSt Is(50) = 3.54MPa	o
10						Defects: -Joint at 10°-20° (2/m) -Joint at 30°-40° (4-5/m) -Joint at 70° (2/m) (See over)						

REMARKS *Point load failed along existing defect

LOGGED BY
JA/DC

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH C39**
SHEET **3** of **3**
REFERENCE No **H11048**

PROJECT **Bruce Highway Upgrade (Cooroy to Curra) Section C**
LOCATION **Cut 10/Woondum Rd Overpass Pier 2** COORDINATES **471594.1 E: 7094777.5 N**
PROJECT No **FG5799** SURFACE R.L. **79.20m** PLUNGE **-90°** DATE STARTED **25/6/11** GRID DATUM **MGA94**
JOB No **232/10A/2** HEIGHT DATUM **AHD** BEARING DATE COMPLETED **26/6/11** DRILLER **Drillsure Pty Ltd**


DEPTH (m)	R.L. (m)	AUGER Casing Wash Boring Core Drilling	RQD (%)	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	59.20										
21			100 (22)		DOLERITE (SW):Cont'd					J, 40°, Pl, T, S, Clnf J, 70°, Pl, T, SR, Clnf Is(50) = 7.00MPa HW, Altered Seam, 60° J, 50°, Pl, T, S, QZ J, 60°, Pl, T, Clnf	x
22			100 (50)		22.4: Becoming coarse grained	SW				BZ, J's, Subvertical	
23			100 (71)							J, 10°, Pl, O, R, Clnf	
24										Is(50) = 3.04MPa Is(50) = 5.90MPa DD = 2.67t/m³; MC = 0.9%; J, 20°, Pl, R, Clnf UCS=72MPa	o x UCS
25	54.35		100		Borehole terminated at 24.85m					HW Brecciated Zone	
26											
27											
28											
29											
30											

REMARKS *Point load failed along existing defect

LOGGED BY
JA/DC

CORE PHOTO LOG - BH C39

Project Name:	BRUCE HIGHWAY UPGRADE - SECTION C		
Project No.:	FG5799	Date:	08/09/2011
Details:	Cut 10	Start Depth (m):	1.50
Reference No.:	H11048	Finish Depth (m):	24.85



SCALE 1:5

CORE PHOTO LOG - BH C39


Project Name:	BRUCE HIGHWAY UPGRADE - SECTION C		
Project No.:	FG5799	Date:	08/09/2011
Details:	Cut 10	Start Depth (m):	1.50
Reference No.:	H11048	Finish Depth (m):	24.85



SCALE 1:5

CORE PHOTO LOG - BH C39

Project Name:	BRUCE HIGHWAY UPGRADE - SECTION C		
Project No.:	FG5799	Date:	08/09/2011
Details:	Cut 10	Start Depth (m):	1.50
Reference No.:	H11048	Finish Depth (m):	24.85



SCALE 1:5