

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No **BH13**

SHEET **1** of **2**

REFERENCE No **H9790**

PROJECT Caboolture River Bridge Foundation Investigation

LOCATION Pier 2 - 15.2m right (along skew) of existing southbound bridge C/L

COORDINATES 497603.4 E; 7003510.0 N

PROJECT No FG5439

SURFACE R.L. 2.53

DATE STARTED 16/11/05

DATUM MGA94 Zone 56

JOB No 25/10A/60C

DATUM AHD

DATE COMPLETED 16/11/05

DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	ALGER Casing WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	2.53											
1						Sandy CLAY (Alluvium): Brown, slightly moist, stiff, medium plasticity, fine grained sand, some silt, some organic matter including plant roots, and visible bioturbation.	CI				4,6,6 N=12	SPT
2												
3	-0.08					Clayey SAND (Alluvium): Dark grey, moist, very loose, fine to medium grained, medium plasticity, lots of organics including black decomposed plant matter, some orange ironstaining.	SC				1,1,1 N=2	SPT
4	-1.08					Highly organic layer at 3.5-3.6m, possibly an old tree intersected.						
5	-2.48					Clayey Gravelly SAND (Alluvium): Pale grey-brown, moist, loose to medium dense, medium to coarse grained, fine gravel up to 6mm, some medium plasticity brown clay, trace of medium gravel.	SP				3,5,5 N=10	SPT
6	-3.68					Gravelly SAND (Alluvium): Grey-brown, wet, loose, coarse grained, fine gravel up to 4mm.	SP				2,3,3 N=6	SPT
7	-4.63					Sandy GRAVEL (Alluvium): Grey-brown, wet, loose, fine to medium gravel up to 10mm, coarse grained sand.	GP					
8	-5.78					SANDSTONE: HW:	HW				9,30/80,- N>50	SPT
9						MW:	MW				Very hard to drill from 8.3m. No sample recovered.	30/50,- N>50
10	-7.48										✓ Pile Tip - 7.0	

REMARKS

LOGGED BY
A O'Rourke



Queensland
Government

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No BH13

SHEET 2 of 2

REFERENCE No H9790

PROJECT Caboolture River Bridge Foundation Investigation

LOCATION Pier 2 - 15.2m right (along skew) of existing southbound bridge C/L

COORDINATES 497603.4 E; 7003510.0 N

PROJECT No FG5439

SURFACE R.L. 2.53

DATE STARTED 16/11/05

DATUM MGA94 Zone 56

JOB No 25/10A/60C

DATUM AHD

DATE COMPLETED 16/11/05

DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	-7.48											
11						SANDSTONE: As above. SW: Pale grey, medium grained, medium strength, trace of orange-brown ironstaining in places, occasional bands of dark grey siltstone rip-up clasts and thin black coal laminae, occasional low strength MW bands. Defects: Occasional subhorizontal bedding partings. 70° irregular joint.	SW				Is(50)=0.49 MPa Is(50)=0.62 MPa	x o
12							MW				Is(50)=0.24 MPa	o
13	-10.48		81			Core loss 12.43-13.0m (left down hole).	SW				11.57-11.85m: Conglomerate band containing grey siltstone rip-up clasts.	
14						Borehole terminated at 13m					12.24m: 70° joint, irregular, rough. Is(50)=0.35 MPa Is(50)=0.58 MPa	x o
15												
16												
17												
18												
19												
20												

REMARKS

LOGGED BY
A O'Rourke

Project: FOUNDATION INVESTIGATION FOR THE WIDENING OF THE CAPTAIN
WHISH BRIDGES (NORTH AND SOUTHBOUND) – CABOOLTURE RIVER


Borehole No: BH13 Pier 2

Start Depth: 10.00m

Finish Depth: 13.00m

Project No: FG5439

H No: 9790



SCALE 1:5

F:GEOT043/1



Point Load Strength Index - Test Report

Project: CABOOLTURE RIVER BRIDGE

Project No: FG 5439

Date Sampled 16/11/05

Feature: PIER 2

Sample Type: NMLC ROCK CORE

Date Tested 14/12/05

Report No. FG 5439/12/GS05/821AS4133.4.1

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS05/821-A	BH13	10.12	D	0.50	0.49	M	Sandstone
GS05/821-B	BH13	10.16	A	0.69	0.62	M	Sandstone
GS05/821-C	BH13	10.98	A	0.27	0.24	L	Sandstone
GS05/821-D	BH13	12.29	D	0.36	0.35	M	Sandstone
GS05/821-E	BH13	12.32	A	0.66	0.58	M	Sandstone

Sample Remarks

* D - Diametral; A - Axial; B - Block; I - Irregular;

** EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High (taken from AS1726 Table 8A)

Remarks / Variations to Test Procedures:

Test Method: AS4133.4.1

Software Version 2.03 April 2005

Client Name: RS&E STRUCTURES DIVISION

Client Address: PO BOX 1412 SPRING HILL 4001

Signatory

(P.REYNOLDS)



Accreditation Number: 2302
Accredited for compliance
with ISO/IEC 17025

This document is issued in
accordance with NATA's
accreditation requirements.