## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



## **ENGINEERING BORELOG**

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95

BOREHOLE	No	:	129
SHEET		:	1 OF 1
REFERENCE :	No	:	н8196

PROJ	ECT	:	SOUTH E	AST	TRANSIT PROJECT-SECTION 1						
LOCA	TION	:?	612.99	ŧΕ	163657.58N						
PROJ	ECT No	:9	60128		SURFACE R.L.: 20.04			DR	ILL	ER : DALY BROTHERS PTY LTD	
JOB 1	No	:			DATUM : AHD			DATE DR	ILLI	ED: 3/2/98	
DEPTH (m)	R.L. (m)	SER SING SING	RQD ()%	SAMPLE	MATERIAL DESCRIPTION	GATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA  AND  TEST RESULTS	SAMPLES
0	20.04	\$086	REC*	SAN		WEA	⋣⋧∓≅¬ <u>२</u>	88888	G. H.		SAI
	19.74				BITUMEN / ASPHALT			<u> </u>		Driller's log only.	‡
- - - - - - - - - - - - - - - - - - -					FILL Brown to grey, silty gravel (Probable engineered /subgrade fill)	GC				2,2,2 N=4	SPT
3	18.24				SANDY SILTY CLAY Yellow brown to mottled grey. Angular to subangular medium to coarse quartz grains; some occasional relic rock stru- ctures. (Probable residual type material).	CL				3,2,2 N=4 2,4,3 N=7	SPT :
	16.29 14.71		Administrative of the second		PHYLLITE GREY GREEN TO BLUE GREY MEDIUM TO COARSE GRAINED FOLIATED METASEDIMENTARY ROCK. STEEP FOLIATION PLANE (70-90 DEG.); BOTH CONCORDANT AND DISCORDANT QUARTZ VEINS.  XW: Generally exhibits engineeering properties of brown to yellow brown moist very stiff to hard sandy silty clay.	XW				7,9,13 N=22	SPT
E	14.04		(37%) 45		HW: Mainly corestone and rock kernals in sandy silty clay matrix. Corestones app- ears to be clastic in nature.	HW				Water pressure test from 5.30 to 10.00m; WPT = 6uL	1
-6 -		*	(50%) 100 (66%) 100		MW: Orange brown to grey brown. Frequent concordant and contorted quartz veins to 800mm; partly to completely red brown iron stainning throughout; vertical bedding.					Water Pressure Test from 6.50 to 10.00m; WPT= 5uL Is(50)=0.66MPa	x 7
-7 			(41%)		Defects:  Major - Subhorizontal (<30 deg.)  - At 30 to 40 deg.  Minor - Foliation partings (90 deg.)					Pressuremeter Test at 7.30m Is(50)=2.19MPa	x -
L 8		1	(95%) 100			MW				Is(50)=0.42MPa Is(50)=1.31MPA	x -
- · · · · · · · · · · · · · · · · · · ·			(43%) 100							Is(50)=1.99 <b>M</b> Pa	x -
: - 10	<u>10.</u> 04		(92%) 100							Is(50)=2.16MPa	x -
RE	MARKS	. P	Lease I	efe	r attached sheet/s for defect descriptions	:		•••••		DISS	



## DEFECT DESCRIPTIONS OF BORELOGS

[FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95] BOREHOLE NO: BH129

SHEET: 1 of 1

REFERENCE NO: H8196

PROJECT : SOUTH EAST TRANSIT PROJECT - SECTION 1

LOCATION : 2612.994E 163657.58N

PROJECT NO : C60128 SURFACE R.L : 20.04 DRILLER : DALY BROTHERS P/L

JOB NO : DATUM : AHD DATE DRILLED : 9/1/98

DEPTH	DEFECT TYPE	APPRO. DIP ANGLE (Deg)	PLANARITY	ROUGHNESS	APERTURE	WALL ALTERATION	OTHER
6.65	J	10	p	S	0		
7.10	J	15	St	R	0		
7.12	J	0	15	IR	0	W	Altered Wall
7.14	J	30	St	R	0		· <del>-</del>
7.29	J	10	St	R	Т		
7.42 -7.47		10					QZ
7.55	Fr	10	St - Ir	R	0	CFeSt	
8.03	Fr						QZ
8.40-8.50	BZ						QZ
8.60	J	45	P		T		QZ
8.71-8.91	,					_	QZ
8.75	Fr	30	Ir	R	Т	CFeSt	QZ
8.94	Fr	0	Ir	R	0		<del> </del>
8.40-8.50	BZ						QZ
9.75-10.0	FP	90	Cu	SM	Т	PIrSt	
9.80	J	30	P		Т		

**Abbreviations** 

ROUGHNESS		W	WALL ALTERATIONS		TYPE	OTHER		
R	Rough	FeSt	Iron Stained	J	Joint	P	Partly	
Sm	Smooth	w	Weathered	В	Bedding	QZ	Quartz Vein	
SL	Slickensided			FP	Foliation Parting	Co	Completely	
				Fr	Fracture	In	Incipient	
	PLANARITY APERTURE		SZ	Sheared Zone	SI	Sand Infill		
Pl	Planar	С	Closed	WS	Weathered Seam	H	Horizontal	
St	Stepped	0	Open	CZ	Crushed Zone	V	Vertical	
Un	Undulating	F	Filled	SM	Secondary Mineralisation	CI	Clay Seam	
Cu	Curved	Т	Tight	BZ	Broken Zone	Cn	Clean	
Ir	Irregular			HFZ	Highly Fractured Zone			

NOTE: This sheet should be read in conjunction with appropriate Engineering Borelog.



