COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

MAIN ROADS DEPARTMENT DRILLING REPORT

H 53 FORM 23ZL

	4 10
PROJECT STORY BRIDGE EXPRESSWAY	PROJECT No!9
DISTRICT NO1SHIRE BRISBANE CITY	HOLE No25
ROAD. Main Street	JOB No 298/12/2
LOCATION. 16' South of Prospect St kerb	RL DATUM B.C.C.
10' east of eastern kerb of Main St	
TYPE AND SIZE OF DRILLING .0-3.5' Tricone. Drilling: 3.5'- 16.5'NXM Diamond Drilling.	GROUND SURFACE5.7.4
Drilling; 3.5' - 16.5'NXM Diamond Drilling	ROCK SURFACE49.4
	BOTTOM OF HOLE. 40.9
DATE DRILLED 16th January, 1967	WATER TABLE
	H-realization in the second

DEPTH	% CORE				S	AMPLE
1."= 5 1	REC.	DIAGRAM	STRATA	DESCRIPTION OF SOIL ROCK	No.	TYPE
				brown clayey sand decomposed tuff?		
			FILL	3.5 - 8.0 mainly moderately weathered tuff boulders		
8.0	17	8.0		4.7.		10.5
				light grey to pink rhyolitic tuff		
12.0	100		MODERATELY WEATHERED	infrequent jointing at low to high angle		
-			TUFF	highly ironstained in joints		
16.5	100	16.5		14.5 - 16.5 highly fractured		
				END OF HOLE		

DRILLER C.W. T.McK	PLANT. M.R.D. GEMCO.	93.1.0
REMARKS Hole Cased to 3.5°		ļ

DATE. 6/2/67P.J. ClutterbuckEOLOGIST APPROVED. APPROVED. DATE. 8/2/6.7. (c) State of Queensland (Department of Transport and Main Roads) 2020, CC BY 4.0. Please note copyright and limitation of liability notices on attached cover page.