

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://ggd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH105**
SHEET **1** of **5**
REFERENCE No **11464**

PROJECT Townsville Ring Road Section 4
LOCATION Kalynda Parade Overpass COORDINATES 467751.3 E; 7866487.1 N
PROJECT No FG6020 SURFACE R.L. 14.21m PLUNGE _____ DATE STARTED 27/3/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING ROCK ROLLER WASH BORING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	14.21												
13.91						Sandy SILT (TOPSOIL) Pale brown to grey, moist, soft. Low plasticity, some tree roots.							
1					A	Sandy Silty CLAY Pale brown to grey, moist, very stiff. Mainly low to medium plasticity, fine grained sand.	(CL)					2,9,16 N=25	SPT
2					B							MC = 12.1% LL=28.8% PI=14% LS=9.4% 7,10,14 N=24	SPT
11.51					C	Silty SAND Pale brown to grey occasionally mottled with orange, moist, very dense. Mainly fine to medium grained sand.						14,30/150 N>50	SPT
3					D							16,30/140 N>50	SPT
4					E							24,30/80 N>50	SPT
5					F							24,30/90 N>50	SPT
6					G		(SM)					9,21,30 N>50	SPT
7					H							18,30/120 N>50	SPT
8													
9													
10													

REMARKS _____

LOGGED BY
VP

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH105
SHEET 2 of 5
REFERENCE No 11464

PROJECT Townsville Ring Road Section 4
LOCATION Kalynda Parade Overpass COORDINATES 467751.3 E; 7866487.1 N
PROJECT No FG6020 SURFACE R.L. 14.21m PLUNGE _____ DATE STARTED 27/3/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING ROCK ROLLER WASH BORING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	4.21												
11					J	Silty SAND Cont'd Becoming medium to coarse grained.		(SM)				30/140 N>50	SPT
12	2.21				K	Sandy SILT Pale brown, moist, hard. Low plasticity, fine grained sand.		(ML)				MC=27.9% LL=41.6% PI=11% LS=8.2% 10,15,32 N=47	SPT
13					L							13,28,30/100 N>50	SPT
14	-0.09				M	Silty SAND Pale brown, moist, medium dense to mainly dense. Medium to coarse grained sand.						10,13,13 N=26	SPT
15					N	16.5m-18.0m: Dense to very dense.		(SM)				14,22,32 N>50	SPT
16					P							11,18,28 N=46	SPT
17					Q							12,16,24 N=40	SPT
18													
19													
20													

REMARKS _____

LOGGED BY
VP

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH105**
SHEET **3** of **5**
REFERENCE No **11464**

PROJECT Townsville Ring Road Section 4
LOCATION Kalynda Parade Overpass COORDINATES 467751.3 E; 7866487.1 N
PROJECT No FG6020 SURFACE R.L. 14.21m PLUNGE _____ DATE STARTED 27/3/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING ROCK ROLLER WASH BORING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH						DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
									EH	VH	H	M	J	VL	EL			
20	-5.79					Silty SAND Cont'd										20 60 200 600 2000		
21					R	Becoming fine grained.											7,15,20 N=35	SPT
22																		
23					S		(SM)										9,16,23 N=39	SPT
24						23.3-m - 25.3m: Very dense cemented layer with some gravel.												
25					T												21,30/40 N>50	SPT
26	-11.09				U	Sandy Silty CLAY Pale brown occasionally mottled with orange, moist, hard. Low to medium plasticity, fine grained sand.											MC = 17.6% LL=40% PI=20.2% LS=13% 15,25,30/125 N>50	SPT
27					V												20,30/130 N>50	SPT
28							(CL-CI)											
29					W												23,30/80 N>50	SPT
30																		

REMARKS _____

LOGGED BY
VP

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH105**
SHEET **4** of **5**
REFERENCE No **11464**

PROJECT Townsville Ring Road Section 4
LOCATION Kalynda Parade Overpass COORDINATES 467751.3 E; 7866487.1 N
PROJECT No FG6020 SURFACE R.L. 14.21m PLUNGE _____ DATE STARTED 27/3/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING ROCK ROLLER WASH BORING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
30	-15.79				X	Sandy Silty CLAY Cont'd						20,30/145 N>50	SPT
31													
32					Y		(CL-Cl)					16,29,30/90 N>50	SPT
33					Z							MC = 18.8% LL=24.2% PI=6.6% LS=6.0% 9,14,24 N=38	SPT
34													
35	-20.29				AA	Silty SAND Pale brown to pale grey, moist, very dense. Fine to medium grained sand.						19,24,27 N>50	SPT
36					AB		(SM)					13,21,30/125 N>50	SPT
37													
38					AC							14,25,30/110 N>50	SPT
39	-24.79				AD	GRANITE Medium to coarse grained, intrusive igneous rock of felsic composition HW: Brown to orange, medium to coarse grained, massive, very low strength.		HW				30/70 N>50	SPT
40													

REMARKS _____

LOGGED BY
VP

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH105
SHEET 5 of 5
REFERENCE No 11464

PROJECT Townsville Ring Road Section 4
LOCATION Kalynda Parade Overpass COORDINATES 467751.3 E; 7866487.1 N
PROJECT No FG6020 SURFACE R.L. 14.21m PLUNGE _____ DATE STARTED 27/3/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 2/4/13 DRILLER Cairns Drilling

DEPTH (m)	R.L. (m)	AUGER CASING ROCK ROLLER WASH BORING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
40	-25.79					GRANITE HW: Cont'd	+	+	HW					
	-26.29				AE	Borehole terminated at 40.5m	+	+					No sample recovery	30/20 N>50 OPT
41														
42														
43														
44														
45														
46														
47														
48														
49														
50														

REMARKS _____

LOGGED BY
VP