COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95

BOREHOLE No: 147

SHEET: 1 OF 3

REFERENCE No: H8100

CATION :		DTORWAY LOGAN RIVER SERVICE ROAD BRIDGE FOL id Ref. 19628E 139929N						•••••		
	2/4+	DATUM : AHD					: FOUNDRIL : 4/9/97			
(m) (m) (ER.T.	RQD	MATERIAL .	ПП	INTACT STRENGTH	DEFECT	907	ADDITIONAL DATA			
3.24	SAMPLE	DESCRIPTION	USC	⊒¥≖≅⊐Ş	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	GRAPHIC	TEST RESULTS	SAMPLES		
1		GRAVELLY SILTY CLAY Brown to dark brown moist soft to stiff (probable fill material).	CL				28,5,4 N=9	SPT		
1.24		SILTY CLAY Dark brown to dark grey, moist very soft to stiff alluvium. High organic content.	СН				1,-, N<1 Peak Su=36.6kPa Res Su=18.3kPa	SPT		
-3.01			CA				SuPP=0.36kPa Peak Su=29.3kPa Res Su=13.7kPa	FSV		
3,01		GRAVELLY SAND Pale brown to grey wet coarse alluvium. Minor silt bands in parts. Peaty bands to 100mm thick common.	G₩				2,4,4 N=8	SPT SPT		
0 -6.76 REMARKS :	Other - Was	shboring rom pocket penetrometer reading. partment of Transport and Main Roads) 2020, CC BY 4.0					LOGGED BY			



ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95

BOREHOLE No : 147

SHEET : 2 OF 3

REFERENCE No : H8100

ECT No No				SURFACE R.L.: 3.24 DATUM: AHD						ER : FOUNDRIL ED : 4/9/97
R.L. (m)	AUGER CORE DRIL CASING OTHER	RQD ()%	SAMPLE	MATERIAL DESCRIPTION	П	THERING S	NTACT TRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS
-7.76				(Cont'd)	GW	,				3,4,5 N=9
				CLAYEY SAND Grey to brown grey, medium dense alluvium.						6,9,12 N=21
					sc					8,10,9 N=19
12.01										Fine poorly graded condensed layers. 5,4,6 N=10
13.96				GREYWACKE GREY MEDIUM GRAINED, METASEDIMENTARY ROCK. XW: Grey brown to yellow brown generally exhibits engineering properties of silty clay to clayey sand.	хw	,				9,14,30/120 N>50
13.96		100		SW: Brown ironstaining only along defects.Otherwise as per MW.Defects mainly 30-70 degrees thinly coated with clay in few defects.	SW	7	***************************************			Is (50) =5.06MPa Is (50) =>5.8MPa
16.76	- 88 ∶									Is(50)=>7.2mPa Is(50)=>5.8mPa



ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95 BOREHOLE No : 147

SHEET : 3 OF 3

REFERENCE No : H8100

LOCA	TION				Ref. 19628E 139929N				N	•••••	••••••	•••••	
					SURFACE R.L. :				RILLEF	: .F	OUNDRIL	••••••	
JOB		2/1+					DRILLER : FOUNDRIL DATE DRILLED : 4/9/97						
	R.L. (m) -16.76	CORE DRIL CASING OTHER		SAMPLE	MATERIAL DESCRIPTION	nsc	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG		ADDITIONAL DATA AND TEST RESULTS	SAMPLES	
	-16.96	1881 :	100	****	END OF HOLF	 ╁	: : : : : -	- : : : :		_		+ -	
-21 -22 -24 -25 -27					END OF HOLE								
30							Liiii	-::::					
RE	MARKS	·				 					LOGGED BY		

(c) State of Queensland (Department of Transport and Main Roads) 2020, CC BY 4.0. Please note copyright and limitation of liability notices on attached cover page.

