

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH56
SHEET 1 of 2
REFERENCE No H11095

PROJECT Moreton Bay Rail Link
LOCATION Halpine Lake Bridge 9, Abutment A, Ch.6000 COORDINATES 502868.4 E; 6986475.0 N
PROJECT No FG5921 SURFACE R.L. 17.00m PLUNGE _____ DATE STARTED 21/7/11 GRID DATUM MGA94 Zone 56
JOB No 250/120/3 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 21/7/11 DRILLER R&D Drilling Pty Ltd

D:\D.D.M.R.LIB_01\A.GLB Log A.ENGINEERING BOREHOLE LOG W LITHOLOGY FG9921 MORETON BAY RAIL LINK.GPJ <<DrawingFlex>> Dalgal CPT Tool gINI Add-In 06/10/2011 14:46															
DEPTH (m)	R.L. (m)	AUGER CORE DRILLING	RQD () %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS	
0	17.00		CORE REC %												
	16.40				Silty SAND (Topsoil) Dark grey, moist, soft.							Based on Driller's logs only			
1				A	Sandy SILT (Residual) Yellow red brown, moist, stiff to very stiff. Sand fraction fine to medium grained; ferrigenous iron stained nodules <10mm. Becoming more sandy below 2m depth.	(CL-ML)						3,5,6 N=11	SPT		
2				B								5,7,8 N=15	SPT		
3	14.00			C	SANDSTONE Fine to medium grained, massive, poorly cemented sedimentary rock mainly comprising of sand sized particles XW: Generally exhibits engineering properties of yellow and grey, moist, fine to medium grained, mainly medium dense silty sand.	XW						Minor clay fraction and iron staining throughout. 16,27,30/110mm N>50	SPT		
4	13.50				HW: White grey and red brown, fine to medium grained, massive with slightly laminated, very low to low strength.										
5					Contains highly iron stained bands below 5.6m depth.										
6					Occasional subangular, high strength quartzitic gravel sizing <40mm; soft clay bands between 6m - 7.5m approx. 200mm thick.										
7					Broken zone below 5.3m approx. 350mm long. Defects: - Drilling-induced bedding / lamination partings @ 0-5° (2-3/m) - Joint @ 20° (1/m) - Joint @ 45° (2-3/m)	HW						Is(50) = 0.72MPa Is(50) = 0.42MPa	x o		
8					Defect surfaces are close to medium spaced, irregular, slightly rough, open, closed, clay infilled or iron stained. Contains ferruginous iron stained bands throughout.							Is(50) = 0.50MPa Is(50) = 0.52MPa Is(50) = 0.17MPa Is(50) = 0.15MPa DD = 2.02t/m³; WD = 2.22t/m³; MC = 9.8%; UCS - 1.4 MPa Is(50) = 0.06MPa Is(50) = 0.13MPa	x o x o	UCS	
9												J, 45°, Clay infill	Is(50) = 0.08MPa Is(50) = 0.16MPa	x o	
10					(See over)							J, 20°, Carb infill	Is(50) = 0.86MPa Is(50) = 1.05MPa	x o	

REMARKS _____

LOGGED BY
BW/LVD



ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH56
SHEET 2 of 2
REFERENCE No H11095

PROJECT Moreton Bay Rail Link
LOCATION Halpine Lake Bridge 9, Abutment A, Ch.6000 COORDINATES 502868.4 E; 6986475.0 N
PROJECT No FG5921 SURFACE R.L. 17.00m PLUNGE DATE STARTED 21/7/11 GRID DATUM MGA94 Zone 56
JOB No 250/120/3 HEIGHT DATUM AHD BEARING DATE COMPLETED 21/7/11 DRILLER R&D Drilling Pty Ltd


DEPTH (m)	R.L. (m)	AUGER CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
10	7.00					SANDSTONE HW: (Cont'd)							Is(50) = 0.14MPa Is(50) = 0.06MPa	x	o
11			100				HW								
12	5.40		100			MW: Mottled yellow red grey, fine to medium grained, massive and laminated, low to medium strength. HW, very low strength bands below 14.4m, approx. 900mm long; iron staining along lamination. Dark black carbonaceous (coal seams) bands below 14.75m, approx. 250mm long.							DD = 2.08t/m ³ , WD = 2.24t/m ³ , MC = 7.4%; UCS - 2.1MPa Is(50) = 0.26MPa Is(50) = 0.24MPa J, 20° Is(50) = 0.20MPa Is(50) = 0.13MPa J, 45°, Fest Is(50) = 0.29MPa Is(50) = 0.18MPa HW, very low strength Carb bands	UCS	x o x o x o
13			100				MW								
14			100												
15	2.00		100			Interbedded MUDSTONE and SILTSTONE SW: Dark grey to black, fine grained, laminated, mainly high strength. Contains thin bands of coal seams below 17m. Defects: - Drilling-induced lamination and bedding partings @ 0-5° (3-4/m) - Joint @ 20° (1-2/m) Defect surfaces are planar and irregular, smooth and slightly rough, open and closed, clay or carbonaceous infill.							Is(50) = 0.88MPa Is(50) = 1.49MPa Is(50) = 1.08MPa Is(50) = 3.35MPa 3 x Js, 20° Is(50) = 0.48MPa Is(50) = 1.43MPa Is(50) = 0.42MPa Is(50) = 2.12MPa Is(50) = 0.93MPa Is(50) = 4.23MPa Is(50) = 0.86MPa Is(50) = 3.49MPa		x o x o x o x o x o x o
16			100				SW								
17			100												
18	-1.50		100										DD = 2.40t/m ³ , WD = 2.54t/m ³ , MC = 2.6%; UCS - 21.7MPa		
19						Borehole terminated at 18.5m									
20															

REMARKS

LOGGED BY
BW/LVD



Project Name	Moreton Bay Rail Link (MBRL)		
Project No	FG5921	Date	21/07/11
Borehole No	BH 56	TMR H No	
Location	Halpine Lake Rail Bridge	Start Depth (m)	3.50
Detail	Abutment A Structure	Finish Depth (m)	18.50
Chainage	6006	Submitted By	BW
Remarks			



0 100 200 300 400 500 600mm

SCALE 1:5