#### **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

### **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



EB

## **ENGINEERING BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/5-2009 BOREHOLE No \_BH106 SHEET \_1\_ of \_3\_ REFERENCE No H10688

**PROJECT** BRUCE HIGHWAY (COORDY - CURRA) SECTION A GEOTECHNICAL INVESTIGATION LOCATION Cut 14 COORDINATES 484181.9 E; 7081226.9 N SURFACE R.L. \_\_155.18m PLUNGE \_\_\_\_\_ PROJECT No FG5825 DATE STARTED \_11/2/10\_ GRID DATUM MGA94 JOB No 128/10A/901 HEIGHT DATUM AHD BEARING DATE COMPLETED 15/2/10 DRILLER Drillsure RI ROD INTACT DEFECT (m) ()% STRENGTH SPACING ADDITIONAL DATA E MATERIAL AND GRAPHIC AÚGER CASING WASH B CORE D DESCRIPTION TESTS SAMPL CORE **TEST RESULTS** REC % 155.18 0 11111 Silty Clay Brown to mottled red, moist, stiff. Intermediate plasticity; rock fabric visible in 4,5,7 parts. (CI) SPT N=12 153.68 PHYLLITE (XW): giNt Add-In 20/05/2010 14:21 6,11,20 SPT Generally exhibits the engineering N=31 properties of mottled pale grey to red -2 brown, moist, hard, gravelly Silt. XW Quartz veins up to 50mm thick; rock fabric visible throughout. 13,26,30/40mm C SPT N>50 CPT Tool 152.18 (0)PHYLLITE (HW): Datgel Brown, fine grained, foliated. GDW. Foliations are indistinct. HW DWG71494 100 Crushed quartz throughout. (0) COOROY-CURRA SECTION A BHS.GPJ 150.73 100 PHYLLITE (MW): (0) □ Clay seam Brown, fine grained, foliated. Foliation is indistinct. 100 Crushed QZ seams and clay (0)Defects are generally closely spaced. Defect sets dip at 10° and 60°. Defect 79 (14)surfaces are typically clay infilled. MW -Clay seam, 10° BRUCE HWY Prominent quartz veining and clayey Crushed QZ seam and clay -6 weathered zones. CLy HW zone FG5825 B – BZ 100 148.38 (22)A\_ENGINEERING BOREHOLE LOG W LITHOLOGY PHYLLITE (MW - SW): Dark grey with distinctive light brown Is(50) = 0.78MPa 100 0 mottling, fine grained, foliated Is(50) = 0.90MPa(20) Foliation typically dips at 10 - 30°. 100 ☐ Clay seam Defects are generally medium spaced. (71) Prominent defect set dipping parallel to -8 foliation with other sets at 10° and 45° UCS= 5.3 MPa UCS Defect surfaces are typically clay infilled or Is(50) = 0.59MPaMW 100 iron stained. SW 100 Clay seam, 30° (0) Quartz veins throughout. (30) CLy BZ
Clay seam, 10° Log \_ 0 GLB Is(50) = 0.52MPaIs(50) = 0.63MPa0 OLD 100 REMARKS Standpipe piezometer installed at base of hole. LOGGED BY JA



# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/5-2009

BOREHOLE No \_\_\_BH106\_\_\_

SHEET \_\_2\_ of \_\_3\_\_

REFERENCE No \_\_\_H10688\_\_\_

	BRUCE HIGHWAY (COOROY - CURRA) SECTION A GEOTECHNICAL INVESTIGATION										
	<u>Cut 14</u>								OORDINATES 484181.9 E; 7081226	. <u>9 N</u>	
			SURFACE R.L. 155.18m PLUNGE _								
R.L. (m)	BORING DRILLING ( ) %		MATERIAL	>	NG.	INTACT STRENGTH	DEFECT SPACING (mm)	907	ADDITIONAL DATA		
DEPTH (m)		SAMPLE	DESCRIPTION	LITHOLOGY	THERING		0	GRAPHIC LOG	AND	SAMPLES	
10 145.18	SON CORE	SAM		LITH	USC	파울프론기식의	2000	GRAI	TEST RESULTS	SAMPLI	
-	(0)		PHYLLITE (MW - SW):	***		200			-BZ		
	(42)		(Cont'd)	<b>***</b>			<b>b</b>	1111			
E I I				***			$\vdash$			-	
F.,				<b>***</b>			Ħ:				
[ ]	100		11.0-11.2m: Clayey broken zone	***					CLy BZ	-	
-	(0)			***					□-Jt, 70°, Pl, C, Cln		
				***			Ш,		Is(50) = 0.26MPa	x -	
-				***					Is(50) = 0.62MPa		
<u></u> 12				***			H		├── Clay seam, 20°	-	
	100			***							
E I I	(9)			***						-	
				***							
-13 -				<b>***</b>						1 7	
[				***							
FIII				<b>***</b>					⇒- Clay seam	-	
				<b>***</b>							
- 14 -	100			$\approx$					Is(50) = 0.09MPa		
	(22)			***					Is(50) = 0.87MPa	X -	
				$\approx$						-	
				***					Jt, 30°, Pl, C, CInf		
- 15 -				<b>***</b>	MW- SW					-	
				***							
-	100			<b>***</b>						-	
	(56)			***		3.5					
- 16 -				$\approx$			<b>5</b>			-	
				***			<b>玉</b> :		Is(50) = 1.32MPa Is(50) = 0.86MPa	x :	
-				$\bigotimes$					UCS= 2.2 MPa		
				***							
- 17 -				$\bigotimes$			<b>力</b>			-	
	(66)			<b>***</b>		2.0	4				
-				$\bigotimes$			<del></del>			-	
				$\bowtie$		2 2	10 to		Is(50) = 0.69MPa	x -	
-18				$\approx$		1.8			Is(50) = 0.91MPa	0 -	
				<b>***</b>						]	
	100		18.5-20.25m: Clayey broken zone with	$\bigotimes$			T			-	
	(0)		multiple quartz veins.				Ц: :-			-	
-19	(0)			$\bigotimes$			T				
							J		- CLy BZ		
	60	$\stackrel{\sim}{\rightarrow}$		$\bowtie$			ī			_	
- 20	100			<b>***</b>			1			-	
REMARKS		met	er installed at base of hole.	<u>~~</u>				шШ	LOGGED BY		
	JA										



FG5825 BRUCE HWY

### **ENGINEERING BOREHOLE LOG**

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/5-2009

BOREHOLE No \_\_BH106\_\_ 3 of 3 SHEET REFERENCE No H10688


BRUCE HIGHWAY (COORDY - CURRA) SECTION A GEOTECHNICAL INVESTIGATION **PROJECT** LOCATION Cut 14 COORDINATES 484181.9 E; 7081226.9 N SURFACE R.L. 155.18m PLUNGE \_\_\_\_ DATE STARTED \_11/2/10\_\_ PROJECT No FG5825 GRID DATUM MGA94 JOB No 128/10A/901 HEIGHT DATUM AHD BEARING \_\_\_\_\_ DATE COMPLETED 15/2/10 DRILLER Drillsure R.L RQD INTACT DEFECT AUGER CASING WASH BORING CORE DRILLING ADDITIONAL DATA (m) ()% STRENGTH SPACING 00 E MATERIAL (mm) AND GRAPHIC DESCRIPTION TESTS SAMPL CORE **TEST RESULTS** JSC REC % 20 135.18 (0) PHYLLITE (MW - SW): -CLy BZ (Cont'd) 100 Is(50) = 0.54MPaх (28) Crushed QZ vein Is(50) = 0.31MPa 0 ☐ CLy QZ vein -2 21.27-22.65m: Clayey broken zone and quartz veining. 100 glNt Add-In 20/05/2010 14:21 (0) CLy BZ -22 100 (0) 89 (31) I CPT Tool UCS= 3.3 MPa UCS ls(50) = 0.18MPaDatgel ( 100 DWG71494.GDW (43) -24 COOROY-CURRA SECTION A BHS.GPJ 100 MW - 25 (21)25.6-26.6m: Clayey broken zone 90 CLy BZ (0) (0) 100 ENGINEERING BOREHOLE LOG W LITHOLOGY 26.8-27.1m: Clayey broken zone - CLy BZ (29)-27 Is(50) = 0.57MPa0 Is(50) = 0.80MPa- QZ vein 100 -28 BZ and QZ veining (0) 100 (0) CLy BZ 100 引\_29 Is(50) = 0.59MPa(79) Is(50) = 0.21MPa UCS= 5.3 MPa 01.GLB UCS 9 PMR. 100 REMARKS Standpipe piezometer instance te main ated at 30m LOGGED BY JA

Project: Bruce Highway Upgrade (Cooroy - Curra) Section A

Borehole No: BH 106
Start Depth: 3.00m

Finish Depth: 30.00m Project No: FG5825 H No: 10688






Project: Bruce Highway Upgrade (Cooroy - Curra) Section A

Borehole No: BH 106
Start Depth: 3.00m
Finish Depth: 30.00m

Project No: FG5825 H No: 10688





Project: Bruce Highway Upgrade (Cooroy - Curra) Section A

Borehole No: BH 106
Start Depth: 3.00m
Finish Depth: 30.00m

Project No: FG5825 H No: 10688



