

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No. **BH20**

SHEET **1** of **2**

REFERENCE No. **H9798**

PROJECT Caboolture River Bridge Foundation Investigation

LOCATION Abutment B - 14.5m right (along skew) & 6.6m north of existing sthbound bridge C/L

COORDINATES 497594.2 E; 7003652.2 N

PROJECT No FG5439

SURFACE R.L. 10.34

DATE STARTED 02/11/05

DATUM MGA94 Zone 56

JOB No 25/10A/60C

DATUM AHD

DATE COMPLETED 02/11/05

DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	ALGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	10.34											
1						Sandy CLAY (Residual Soil): Dark red-brown, moist, stiff, medium plasticity, fine grained sand, some organic matter and bioturbation.	CI				3,6,6 N=12	SPT
2	8.34					SANDSTONE: XW: Pale grey with orange-brown and red-brown staining, fine to medium grained, extremely low strength. Has the soil properties of a sandy clay, moist, stiff to hard, low to medium plasticity, fine to medium grained sand.					4,6,8 N=14	SPT
3											9,13,21 N=34	SPT
4											14,23,22 N=45	SPT
5												
6						Pale grey silstone band 5.5-5.8m. Some red-brown iron-cemented nodules between 5.8-5.95m.	XW				6,8,13 N=21	SPT
7											4,7,11 N=18	SPT
8												
9												
10	0.34											

REMARKS

LOGGED BY
A O'Rourke

ENGINEERING BOREHOLE CABOOLTURE R BRIDGE WIDENINGS GPJ QLD MAIN ROADS GDT 23/02/06



Queensland
Government

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/3-2005

BOREHOLE No BH20

SHEET 2 of 2

REFERENCE No H9798

PROJECT Caboolture River Bridge Foundation Investigation

LOCATION Abutment B - 14.5m right (along skew) & 6.6m north of existing sthbound bridge C/L

COORDINATES 497594.2 E; 7003652.2 N

PROJECT No FG5439

SURFACE R.L. 10.34

DATE STARTED 02/11/05

DATUM MGA94 Zone 56

JOB No 25/10A/60C

DATUM AHD

DATE COMPLETED 02/11/05

DRILLER Drillsure Pty Ltd

DEPTH (m)	R.L. (m)	ALGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	0.34											
11	-0.66					SANDSTONE: XW: As above.	XW				7,11,16 N=27	SPT
12						HW: Pale orange-brown, ironstained throughout, fine to medium grained, very low strength.	HW				13,30/120,- N=50	SPT
13	-2.16					MW: Orange-brown, ironstained throughout, medium grained, low to medium strength, occasional dark brown subhorizontal laminations.						
14						Defects: Occasional subhorizontal bedding partings.	MW				No sample recovery. 30/30,- 13.1-13.30m: Numerous silstone rip-up clasts up to 80mm in diameter.	SPT
15	-5.06										Is(50)=0.07 MPa Is(50)=0.17 MPa	x o
16						SW: Pale grey, medium grained, medium strength, trace of orange-brown ironstaining, occasional thin subhorizontal black coal laminae and dark grey silstone rip-up clasts. 15.75 - 16.3m: Iron stained orange-brown throughout.					15.75-15.77m: Dark brown carbonaceous band. Is(50)=0.99 MPa Is(50)=1.24 MPa	x o
17							SW				16.30-16.40m: Numerous thin black coal laminae.	
18						Coarse grained below 17.6m.					17.30-17.35m: Black vitreous coal laminae.	
19	-8.76					Defects: Occasional planar subhorizontal bedding partings.					18.54-18.68m: Broken zone. Numerous drilling-induced medium to high angle fractures. Numerous silstone rip-up clasts.	x o
20						Borehole terminated at 19.1m						

REMARKS

LOGGED BY
A O'Rourke

Project: FOUNDATION INVESTIGATION FOR THE WIDENING OF THE CAPTAIN WHISH BRIDGES (NORTH AND SOUTHBOUND) – CABOOLTURE RIVER


Borehole No: BH20 Abutment B

Start Depth: 13.10m

Finish Depth: 18.10m

Project No: FG5439

H No: 9798



SCALE 1:5

F:GEOT043/1



Point Load Strength Index - Test Report

Project: CABOOLTURE RIVER BRIDGE

Project No: FG 5439

Date Sampled 2/11/05

Feature: ABUT B

Sample Type: NMLC ROCK CORE

Date Tested 9/12/05

Report No. FG 5439/8/GS05/819AS4133.4.1

Sample Number	Sample Location	Depth (m)	Test Type D,A,B,I*	Is (MPa)	Is50 (MPa)	Strength Descriptor**	Lithology
GS05/819-A	BH20	14.07	D	0.07	0.07	VL	Sandstone
GS05/819-B	BH20	14.10	A	0.20	0.17	L	Sandstone
GS05/819-C	BH20	15.81	D	0.99	0.99	M	Sandstone
GS05/819-D	BH20	15.84	A	1.35	1.24	H	Sandstone
GS05/819-E	BH20	18.40	D	0.69	0.69	M	Sandstone
GS05/819-F	BH20	18.43	A	0.93	0.84	M	Sandstone

Sample Remarks

* D - Diametral; A - Axial; B - Block; I - Irregular;

** EL - Extremely Low; VL - Very Low; L - Low; M - Medium; H - High; VH - Very High; EH - Extremely High (taken from AS1726 Table 8A)

Remarks / Variations to Test Procedures:

Test Method: AS4133.4.1

Software Version 2.03 April 2005

Client Name: RS&E STRUCTURES DIVISION

Client Address: PO BOX 1412 SPRING HILL 4001

Signatory

(P. Reynolds)

19/12/05

Accreditation Number: 2302
Accredited for compliance
with ISO/IEC 17025This document is issued in
accordance with NATA's
accreditation requirements.