

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://ggd.org.au/>

ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM BQF 075:191/95

BOREHOLE No : 106
SHEET : 1 OF 1
REFERENCE No : H8178

PROJECT : SOUTH EAST TRANSIT PROJECT-SECTION 1
LOCATION : 2077.272 164454.188
PROJECT No : C60128 SURFACE R.L. : 9.13 DRILLER : DALY BROTHERS PTY LTD
JOB No : DATUM : AHD DATE DRILLED : 23/1/98

DEPTH (m)	R.L. (m)	AUGER CORE DRILLING CORE DRILLING CASING OTHER	RQD (%) CORE REC%	SAMPLE	MATERIAL DESCRIPTION	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	9.13				FILL Consisting dark grey to black, dry to moist, firm to stiff a mixture of gravel sand, silt and clay. Occasional sandy silty clay layers; old brick fragments. (Non-engineered type fill).	GC				2,3,2 N=5	SPT
1	7.38				SILTY CLAY Pale brown to grey brown, moist, stiff. (Probable residual type material)	CL				3,4,5 N=9	SPT
2	6.38				PHYLLITE GREY GREEN TO GREY, MEDIUM TO COARSE GRAINED FOLIATED METASEDIMENTARY ROCK. FOLIATION PLANE <20 DEGREES. DARK (MICA) AND PALE (QUARTZ) INTERLAYERS. BOTH CONCORDANT AND DISCORDANT MEDIUM TO COARSE QUARTZ VEINS. ROCK TENDS TO BREAK ALONG BEDDING PARTINGS.	XW				4,7,10 N=17	SPT
3					XW : Generally exhibits engineering properties of white to grey green, very stiff moist silty clay. Occasional sand to gravel size particles.					5,7,11 N=18	SPT
4	3.95		(0%) 90		HW : Grey brown, mainly core stones and rock kernels in minor sandy silty clay matrix; Occasional medium to coarse quartz grains.	HW				Pressuremeter Test at 5.5m Is(50)=0.16MPa	x
5	2.78		(0%) 82		MW : Grey brown to orange brown, completely to partly ironstaining throughout. Defects : bedding parting.	MW				Is(50)=1.22MPa Is(50)=0.97MPa	o
6	1.24		(14%) 100		SW : Grey to blue green, bedded. Defects : Major bedding partings (0-30 degrees); occasional 70 degrees.	SW				Water Pressure Test from 7.5m to 8.5m Packer Test WPT= 4UL Is(50)=2.27MPa Pressrometer Test at 7.5m	o
7	0.23		(26%) 100							Is(50)=1.35MPa Is(50)=0.77MPa Is(50)=0.84MPa	x x o
8					END OF HOLE						
9											
10											

REMARKS : See attached list for defect descriptions.

LOGGED BY
DISS

DEFECT DESCRIPTIONS OF BORELOGS

[FOR GEOTECHNICAL TERMS AND SYMBOLS
REFER FORM BQF 075:191/95]

BOREHOLE NO :	106
SHEET :	1 of 1
REFERENCE NO :	H8178

PROJECT :	SOUTH EAST TRANSIT PROJECT - SECTION 1		
LOCATION :	2077.272E 164454.188N		
PROJECT NO :	C60128	SURFACE R.L. :	9.13
JOB NO :		DATUM :	AHD
		DRILLER :	DALY BROTHERS P/L
		DATE DRILLED :	15/1/98

DEPTH	DEFECT TYPE	APPRO. DIP ANGLE (deg°)	PLANARITY	ROUGHNESS	APERTURE	WALL ALTERATION	OTHER
6.00	FP	10	Ir	R	O	P FeSt	
6.13	FP	45	Ir	R	C	P FeSt	
6.42	FP	15	Pl	R	C	Co FeSt	
6.63	FP	20	R	R	O	CoW	
6.89 - 7.55	FP	20	Pl	R	O - C	Co - P FeSt	HFZ along BP
7.72-7.76	FP	20	Ir		O	Co FeSt	HFZ along BP
7.76-7.78							Discordant QZ
8.00		15	Ir	R	O	Co FeSt	
8.55	FP	20	Pl		T		
8.60	J	70	Ir	R	O	P - Co FeSt	PCI
8.85	FP	10	Ir	R	O	P FeSt	
8.88	FP	10	Ir	R	O	P FeSt	

Abbreviations

ROUGHNESS		WALL ALTERATIONS		TYPE		OTHER	
R	Rough	FeSt	Iron Stained	J	Joint	P	Partly
Sm	Smooth	W	Weathered	B	Bedding	QZ	Quartz Vein
SL	Slickensided			FP	Foliation Parting	Co	Completely
				F	Fracture	In	Incipient
PLANARITY		APERTURE		SZ	Sheared Zone	SI	Sand Infill
Pl	Planar	C	Closed	WS	Weathered Seam	H	Horizontal
St	Stepped	O	Open	CZ	Crushed Zone	V	Vertical
Un	Undulating	F	Filled	SM	Secondary Mineralisation	CI	Clay Infill
Cu	Curved	T	Tight	BZ	Broken Zone	Cn	Clean
Ir	Irregular			HFZ	Highly Fractured Zone		

NOTE: This sheet should be read in conjunction with appropriate Engineering Borelog.

C60128

