

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH307
SHEET 1 of 3
REFERENCE No 11485

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464709.8 E; 7871566.4 N
PROJECT No FG6020 SURFACE R.L. 12.32m PLUNGE _____ DATE STARTED 24/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 30/4/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	12.32												
12.02						Silty CLAY (TOPSOIL) Brown, moist, soft. Medium plasticity. Some tree roots.							
					A	Sandy CLAY Brown, dark grey, moist, stiff to very stiff. Medium plasticity.	(CI)					3,4,7 N=11	SPT
10.32					B	Some calcareous material at 1.5m.						7,11,15 N=26	SPT
8.82					C	Silty SAND Pale grey, pale brown, moist, very dense. Fine grained sand. Some white calcareous material.	(SM)					10,28,30/140mm N>50	SPT
					D	Sandy SILT Brown, dark grey, moist, hard.						27,30/100mm,HB N>50	SPT
					E							30,30/30mm,HB N>50	SPT
					F	At 5.5m, minor layer of silty sand. Very dense. Fine to coarse grained.	(ML)					25,30/90mm,HB N>50	SPT
4.82					G							15,25,30/115mm N>50	SPT
					H	Clayey SAND Pale brown, pale yellow, pale grey, moist, dense. Fine to coarse grained sand.	(SC)					10,15,17 N=32	SPT
2.32													

REMARKS _____

LOGGED BY
JA

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH307**
SHEET **2** of **3**
REFERENCE No **11485**

PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464709.8 E; 7871566.4 N
PROJECT No FG6020 SURFACE R.L. 12.32m PLUNGE _____ DATE STARTED 24/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 30/4/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
10	2.32				J	Clayey SAND (Cont'd)	(SC)					8,14,23 N=37	SPT
11	1.32				K	Sandy SILT Pale yellow, brown, pale grey, moist, hard. High content of fine grained sand.	(SM)					8,14,20 N=34	SPT
12					L							9,14,20 N=34	SPT
13					M	Clayey SAND Pale grey, pale brown, moist, dense. Fine to coarse grained sand.	(SC)					11,13,20 N=33	SPT
14	-1.68				N							9,15,20 N=35	SPT
15					P	Becoming pale grey, white, pale brown, very dense clayey sand.						16,20,30/130MM N>50	SPT
16													
17													
18	-5.88												
19	-6.78					VOLCANIC BRECCIA Pyroclastic rock consisting of angular fragments embedded in a finer grained matrix. XW: Generally exhibits the engineering properties of brown, yellow, red, moist, very dense clayey sand. HW: (See over)	XW					30/50MM, HB N>50	SPT
20	-7.68											Is(50) = 0.08MPa	o

REMARKS _____

LOGGED BY
JA

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No **BH307**
SHEET **3** of **3**
REFERENCE No **11485**


PROJECT Townsville Ring Road Section 4
LOCATION Stony Creek Bridge COORDINATES 464709.8 E; 7871566.4 N
PROJECT No FG6020 SURFACE R.L. 12.32m PLUNGE _____ DATE STARTED 24/4/13 GRID DATUM GDA 94
JOB No 268/10M/5 HEIGHT DATUM AHD BEARING _____ DATE COMPLETED 30/4/13 DRILLER Saxon Drilling

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD () %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-7.68		(0)		VOLCANIC BRECCIA		HW				Is(50) = 0.28MPa	o
	-7.78		100		HW: (Cont'd)						J, 40°, Pl, O, Clnf	
			(71)		Brown, pink, medium to coarse grained, massive, very low to low strength. Defects: Broken throughout.						UCS=10.2MPa	o
21			100		MW: Brown to pink, medium to coarse grained, massive, medium to high strength.						Is(50) = 0.85MPa	o
			(40)		Defects:						Is(50) = 0.85MPa	o
					- Joints @ 10° - 30° (3/m)							
					- Joints @ 40° (3/m)							
					- Joints @ 70° (1/m)							
					- Clayey seams							
22			100		Defect spacing is mainly medium.						Is(50) = 2.60MPa	o
			(43)		Defect surfaces are generally planar, open, rough, clay infilled.						Is(50) = 2.29MPa	o
			100								Is(50) = 0.21MPa	o
			(25)								Is(50) = 0.87MPa	o
23					24.30 - 24.90m : Becoming brown, fine to medium grained, high strength.						Is(50) = 0.85MPa	o
			100								Is(50) = 2.61MPa	o
			(0)		Becoming grey brown to pink, medium to coarse grained, high to very high strength.						J, 30°, Ir, O, Clnf, 20mm	
			(27)									
24												
25												
26												
27												
28												
29												
30												

REMARKS _____

LOGGED BY
JA

DEPARTMENT OF TRANSPORT & MAIN ROADS
Geotechnical Branch
35 Butterfield Street, HERSTON Qld 4006
Phone 07 3066 3336

[illegible]