COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2021, licensed under the CC BY 4.0 Licence, prepared by Arup". This licence does not apply to logos or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

This log has been contributed to the Queensland Geotechnical Database with the permission of Arup.

ARU	JP)		В	OREHOLE RECORD	Н	G4	4	SHEET 1
Geotech			cation	& Traini	ng Procinct	LO	OGGED BY	PBF	OF 1
	<u> </u>						ATE/S	15.06.0	
CONTRACTOR DRILL MODEL MOUNTING	Mapstone Geotechnical Services ANGLE Vertical Gemco HS7 BEARING - Trailer DIAMETER 100mm						GROUND LEVEL ~RL 11.2m LOCATION Refer Figure 2		
DRILLING	STRATA				MATERIAL DESCRIPTION	CONDITION			OBSERVATION
DCP TEST RESULTS (blows/100mm)	R.L.	DEPTH	GROUP SYMBOL	LEGEND	SOIL TYPE Colour, Plasticity, Grain Size, Minor Components	WATER / MOISTURE	COHESIVE	STENCY NON COHESIVE	SOIL ORIGIN, STRUCTURE, ETC.
AUGER (TC Bit)	11.05 -	0.15	0	7 4 4	Concrete slab.		> o r o >	1>750>	SLAB
(TO Bit)	10.90	0.30			FILL: Sand and Gravel bedding. FILL: Silt and Sand, dark gray, fine grained.	-			FILL
SPT @ 1.0m 3/5/7 N = 12	10.20	1.00	CL		Silty CLAY with gravel: Mottled red brown, orange brown and cream white, medium plasticity.				RESIDUAL
SPT @ 2.5m 27 / 20 for 70mm	9.20	2.00			XW PHYLLITE: Mottled orange brown and cream white, extremely low strength.				XW ROCK
2 / / 20 for / 0mm N = Refusal SPT @ 4.0m 30 for 70mm N = Refusal		-3				-			
	5.70	5.50			End of borehole at 5.50m				
		7		-	-				
NOTES			•			L		Ј ОВ	4724