COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



TMR.GLB Log A_ENGINEERING BOREHOLE LOG W LITHOLOGY JINGI JINGI BH LOGS.GPJ <<DrawingFile>> Datgel CPT Tool glint Add-In 18/12/2014 13:31

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH14
SHEET	_1_ of _3_
REFERENCE No	11848

	JECT					idgesite Investigation					OORDINATES <u>287013.8 E;</u> 7	— — — — - 024337.2 N	 I
						SURFACE R.L. <u>315.34m</u>							
					HEIGHT DATUM AHD BEARING								
o DEPTH(m)	R.L. (m)	AUGER CASING WASH BODING	CORE DRILLING	RQD ()%	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	INTACT DEFECT STRENGTH SPACIF	W (DW VW EW SRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
- 0.20 1	315.14				A	Silty CLAY (TOPSOIL) Dark grey black, moist, soft. Low plasticity. Some sand, gravel and organic matter. Silty CLAY (ALLUVIAL) Dark grey, moist, firm to stiff. High plasticity.		(CL)				1,2,3 N=5 S	- - - - - - - - - - - - - - - - - - -
- 2	312.64				В			(CH				2,4,5 N=9	- - - SPT - - -
-3 - - - - - - - - - - - - -	311.64				С	Sandy CLAY (ALLUVIAL) Brown, grey, moist, very stiff. Low plasticity. Some fine gravel.		(CL)	± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ±			3,8,10 N=18	- SPT - - -
- -4 - - - - - - -					D	Clayey SAND (ALLUVIAL) Brown, grey, moist, dense. Fine to coarse grained sand. Some fine gravel.			± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ± ±		1	1,17,22 N=39	SPT =
- - - - - - - - - -					Е			(SC			1:	2,19,18 N=37	SPT :
-6 - - - - - - - - - - - - - - - - - -	308.44	-			F	Site CLAY (ALLINIAL)					1:	2,16,22 N=38 S	SPT - - - -
- - - - - - - - - - -					G	Silty CLAY (ALLUVIAL) Dark brown, moist, very stiff. Low plasticity.		(CL)				5,7,12 N=19	SPT - - - - - -
8.70	306.64	-			Н	CLAYSTONE (J_Kk)						6,9,13 N=22	- SPT <u>-</u> - -
- 9 					J	XW: Recovered as pale grey brown, moist, hard, silty clay. Low plasticity. Some HW rock fragments. 9.00m: Dark brown iron oxide precipitate.		XW			14,20,30/	130mm S	- SPT - - - -
REMARKS J_Kk = Kumbarilla Beds * For this specimen, the load cell used does not comply with the test method requirements.									LOGGE				



ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH14
SHEET	_2_ of _3_
REFERENCE No	11848

		Bridgesite Investigation		 N
			DATE STARTED 12/7/14 GRID DATUM MGA 94 Zone 5	
			DATE COMPLETED 13/7/14 DRILLER North Coast Dri	
JOB NO		TILIOTT DATOW _AID BLANNO	BATE GOINI ELTED 101/14_ BRILLERY NORTH-GOEST BIT	<u> </u>
R.L. (m)	REDERING ()% ()% ()% () CORE	MATERIAL DESCRIPTION	INTACT DEFECT STRENGTH SPACING (mm) OID HAW STRENGTH SPACING (mm)	SAMPLES TESTS
10 305.34	REC %	S S S S S S S S S S S S S S S S S S S	TEST RESULTS	SA
		K CLAYSTONE (J_Kk) XW: (Cont'd) Becoming white to pale grey.	14,23,30/100mm	SPT -
- - -11				=
		L	9,16,23 N=39	SPT
- - - - 12			11,17,23	-
		M	N=40	SPT :
- 13 - 13		N	XW 19,30/80mm	SPT -
				-
-		14.00m: Becoming pale grey brown.	30/100mm	SPT
5 -				-
- 15 - 15 15	(30)	15.20m: Becoming white with dark brown	30/110mm	SPT _
		pink patches, dry, hard. Some HW claystone zones with very low to low strength. Thin lenses of XW sandstone.		- - - -
16		Some patches of iron oxide precipitate.	HW	-
j - j - j -	100		XW S(50) = 0.01MPa, A	A (16.30m) (16.34m)
- - - - - - - - - - - - - - - - - - -	(16)		HW16.70m-16.95m: HW Claystone. Very low strength.	-
			UCS=2.31MPa	UCS -
	100			- - - -
j - 5 - 2 -			HW 18.54m-18.68m: HW Claystone. Very low strength.	- - - -
- 			xw xw	=
	100			- - -
DEMARKS	3 J_Kk = Kumbari	lla Beds	LOGGED BY	_
KLIVIAINA		nen, the load cell used does not comply with the test		



TMR.GLB Log A_ENGINEERING BOREHOLE LOG W LITHOLOGY JINGI JINGI BH LOGS.GPJ <<DrawingFile>> Datgel CPT Tool glint Add-In 18/12/2014 13:31

ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM F:GEOT 017/8-2014

BOREHOLE No	BH14
SHEET	_3_ of _3_
REFERENCE No	11848

PRO	JECT	_Jingi_	Jingi Cree	ek Br	<u>idgesite Investigation </u>		_						
LOC	ATION	Pier 1	2 - Right	Han	<u>d Side</u>		_				СО	OORDINATES <u>287013.8 E; 7024337.2</u>	2 <u>N</u>
PRO	PROJECT No FG6169 SURFACE R.L. 315.34m PLUNGE DATE STARTED 12/7/14 GF									14 GRID DATUM MGA 94 Zone	56		
JOB					HEIGHT DATUM _AHD BEARING _								
	R.L. (m)	98	RQD ()%						INTACT STRENGTH	DEFECT SPACING	(D	ADDITIONAL DATA	
DEPTH (m)	()	R IG BORING DRILLING	() //		MATERIAL	5		RING	01112110111	(mm)	GRAPHIC LOG		(0
EPT!		RAGE PROBLEM		PLE	DESCRIPTION	LITHOLOGY		THE			PHIC	AND	SAMPLES
20	295.34	AUG CASI WAS COR	CORE REC %	SAMPLE		틸	USC	WEA	STRENGTH TT U>T≥ J=	UO USO≅≷Š∰	GRA	TEST RESULTS	SAMPLE
-	200.01				CLAYSTONE (J_Kk)					T: : : : : :			
					XW: (Cont'd)							Io(50) = 0.07MPa: * I	_]
-							∃×	(W				Is(50) = 0.07MPa; * Is(50) = 0.03MPa; *	A _(20.46m) -
-													-
21	00444		400							-: : : : : :			
21.20	294.14		100		Borehole terminated at 21.2m		+					Is(50) = 0.06MPa; * I Is(50) = 0.04MPa; * I	D _(21.15m) A _(21.20m) -
-										-: : : : : : :			(=,
]
- - 22									<u> </u>	: : : : : : :			_
-										- : : : : : : :			-
									<u> </u>				_
-													-
													-
- 23 -										-			-
-													-
-									1	-			-
]
- 24										-: : : : : : :			-
-									: : : : : 				-
- 1										-			
-										-:::::			-
- 25									: : : : <u> </u>	-: : : : : :			
													-
El]
-										- : : : : : : : : : : : : : : : : : : :			-
									: : : : : +				-
-26 -]
-									: : : : :	- : : : : : : :			-
-										-: : : : : : :			-
]
- 27 -										-: : : : : :			-
													-
-													-
-													-
28										-			-
-									: : : : : <u> </u>	- : : : : : : : : : : : : : : : : : : :			-
									: : : : : : : : : : : : : : : : : : :				_
[: : : : : ‡	·			=
_ 29									: : : : <u> </u>	<u>-</u> : : : : : : : : : : : : : : : : : : :]
									: : : : : ‡	- : : : : : : : : : : : : : : : : : : :			-
<u> </u>									: : : : : +	<u>-</u>			=
										- : : : : : : : : : : : : : : : : : : :			-
30									: : : : : ‡	- : : : : : : : : : : : : : : : : : : :			-
	REMARK	S J_Kk	= Kumba	arilla	Beds							LOGGED BY	
-	•				n, the load cell used does not comply with the te	st meth	hoc	d red	quirements.			MS	
							_	-				-	