COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/

Queensland Government

GEOTECHNICAL BOREHOLE LOG

FINAL 05/06/2018

BOREHOLE No BH102

Sheet 1 of 3

FOR GEOTECHNICAL TERMS AND H13095 REFERENCE No SYMBOLS REFER FORM F:GEOT 017/8-2014 Bohle River pedestrian/cycle bridge PROJECT off Woolcock St, East side of Bohle River COORDINATES 469139.1 E; 7870124.9 N LOCATION DATE STARTED 21/03/2018 FG6560 SURFACE RL 5.96m PLUNGE 90° grid datum 55K PROJECT No DRILLER Saxon / Jez 268/10M/908 HEIGHT DATUM AHD DATE COMPLETED 22/03/2018 JOB No BEARING USCS WEATHERING ADDITIONAL DATA AND TEST RESULTS RQD INTACT DEFECT SPACING SAMPLES TESTS LITHOLOGY SAMPLE STRENGTH DEPTH (RΙ MATERIAL DESCRIPTION (m) CORE REC % ᇁᆂᆂᆂᆿᅼᆿᇛᇬᇬᄛᇂᇂᇕ Sandy SILT (Topsoil) dark grey, moist, very soft, low plasticity, fine grained sand, trace of (ML) 4.96 SILT (Alluvium) N<1 LL=24% PI= 3% MC=26.2% LS= 7% dark brown-grey, moist, soft, low plasticity, trace of fine sand. (ML) <75µm= 68% 3.96 Silty SAND (Alluvium) 21/03/2018 yellow-brown, moist to wet, loose (SM) to very loose, fine to medium 3.26 grained. SPT Silty CLAY (Alluvium) grey mottled dark brown, moist to wet, firm to stiff becoming soft to very soft with depth, medium (CI) plasticity, trace of fine sand. Su(PP)=0 kPa 1.76 LL=33% PI= 18% U50 MC=30.7% LS= 3% SAND (Alluvium) yellow-grey, moist to wet, loose, fine to coarse grained, sub-angular, trace of silt. From 5.5m: Becoming medium N=18 D dense SPT (SP) From 6.5m: Becoming loose, with fine to medium gravel. SPT -1.54GRAVEL (Alluvium) grey white orange, wet, dense, fine grained, angular to sub-angular, trace of sand. (GP) SPT -3.04 Inferred XW-HW Dacite. XW Continued on next sheet REMARKS: Standpipe installed with screen from 7.5 to 9.0m depth. **LOGGED BY REVIEWED BY** Kay Want S. Foley TMR GEOTECHNICAL BOREHOLE LOG - CREATED WITH HOLEBASE SI

Queensland Government

GEOTECHNICAL BOREHOLE LOG

FINAL 05/06/2018

BOREHOLE No BH102

Sheet 2 of 3

FOR GEOTECHNICAL TERMS AND H13095 REFERENCE No SYMBOLS REFER FORM F:GEOT 017/8-2014 Bohle River pedestrian/cycle bridge PROJECT off Woolcock St, East side of Bohle River COORDINATES 469139.1 E; 7870124.9 N LOCATION FG6560 PLUNGE 90° DATE STARTED 21/03/2018 SURFACE RL 5.96m grid datum 55K PROJECT No DRILLER Saxon / Jez 268/10M/908 HEIGHT DATUM AHD DATE COMPLETED 22/03/2018 JOB No BEARING ADDITIONAL DATA AND TEST RESULTS RQD USCS WEATHERING INTACT DEFECT SPACING LITHOLOGY SAMPLES TESTS SAMPLE STRENGTH DEPTH (RΙ MATERIAL DESCRIPTION CORE REC % No sample recovered. XW -5.16 (26)BRECCIATED DACITE MW D (11.29m) HW: Pale pink-brown, fine grained, HW (0) aphanitic, mainly very low to low Is(50)=1.24 MPa strength. (fg) Highly altered, brecciated and (0)broken throughout. HW -Js: 5°-30° (3-5/m), PI/Ro, Cly infill 13 (0) HW (0) Is(50)=0.12 MPa D (13.70m) -7.94 (0)Core Loss 15 -9.14 XW **Brecciated Dacite** (0) XW: Recovered as Gravelly silty 0 CLAY: Pale grey, dry, hard, medium 12/50mm plasticity, fine to medium gravel, XWangular to sub-angular. -10.24 BRECCIATED DACITE HW: green-grey, fine grained, HW D (16.60m) aphanitic, extremely low to low 100 Is(50)=0.12 MPa strength. Highly altered/brecciated. <u>(B)</u> Clay in-filled joints. 17 -11.14 (0) BRECCIATED DACITE D (17.20m) Is(50)=4.22 MPa 88 MW: dark green-grey to brown-(0) grey, fine grained, aphanitic, mainly high strength. Is(50)=0.13 MPa D (17.76m) Highly altered. Broken throughout. (33)Js: 40°-50° (5-8/m), Pl/Ro, TI-OP, some Cly Vr. From 18.06-18.33m: Colour MW Is(50)=4.55 MPa D (18.40m)change green-grey to pink-brown From 18.5m: Js 5°-10° (5/m), Pl/ Ro, TI, some Cly and FeSt. Becoming pink brown. 19 UCS=26.90 MPa (19.00m) 100 Is(50)=0.92 MPa D (19.31m) (0) 100 (0) Continued on next sheet REMARKS: Standpipe installed with screen from 7.5 to 9.0m depth. **LOGGED BY REVIEWED BY** Kay Want S. Foley TMR GEOTECHNICAL BOREHOLE LOG - CREATED WITH HOLEBASE SI

Queensland Government

GEOTECHNICAL BOREHOLE LOG

FINAL 05/06/2018

BH102 BOREHOLE No

Sheet 3 of 3 FOR GEOTECHNICAL TERMS AND H13095 REFERENCE No SYMBOLS REFER FORM F:GEOT 017/8-2014 Bohle River pedestrian/cycle bridge PROJECT off Woolcock St, East side of Bohle River COORDINATES 469139.1 E; 7870124.9 N LOCATION SURFACE RL 5.96m DATE STARTED 21/03/2018 FG6560 PLUNGE 90° grid datum 55K PROJECT No 268/10M/908 HEIGHT DATUM AHD BEARING ° DATE COMPLETED 22/03/2018 DRILLER Saxon / Jez JOB No USCS WEATHERING ADDITIONAL DATA AND TEST RESULTS RQD INTACT STRENGTH DEFECT SPACING LITHOLOGY SAMPLES TESTS DEPTH (m) SAMPLE RΙ MATERIAL DESCRIPTION CORE REC % 표'높'ヸ'ヹ'ヿ゙゙゙゚゚゚ヿ゙゚゚゚゚ヿ゚ゔ゚゚゚゚゚゚ゔヹ゚゚゚゚゚゚゚ヺ゚゚゚゚゚ (0) BRECCIATED DACITE MW: Cont'd. MW 100 Is(50)=2.34 MPa D (20.63m) 20.75m: Clay seam MW Is(50)=1.09 MPa D (22.00m)_ -16.14 100 Borehole completed at 22.10m 23 25 26 27 REMARKS: Standpipe installed with screen from 7.5 to 9.0m depth. **LOGGED BY REVIEWED BY** Kay Want S. Foley TMR GEOTECHNICAL BOREHOLE LOG - CREATED WITH HOLEBASE SI

CORE PHOTO LOG
DEPARTMENT OF TRANSPORT AND MAIN ROADS
GEOTECHNICAL SECTION



Project Name	Bohle River Pedestrian/Cycle Path – Geotechnical Investigation		
Project No.	FG6560	Date	March 2018
Borehole No.	BH102	Reference No.	
Location	SE bank	Start Depth (m)	11.1
Submitted By	K. Want	Finish Depth (m)	22.1







Project Name	Bohle River Pedestrian/Cycle Path – Geotechnical Investigation		
Project No.	FG6560	Date	March 2018
Borehole No.	BH102	Reference No.	
Location	SE bank	Start Depth (m)	11.1
Submitted By	K. Want	Finish Depth (m)	22.1

