

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://ggd.org.au/>



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No **BH23**

SHEET **1** of **5**

REFERENCE No **H9572**

PROJECT **GATEWAY BRIDGE DUPLICATION FOUNDATION INVESTIGATION - GATEWAY UPGRADE PROJECT**

LOCATION **PIER 11 - DOWN STREAM END** COORDINATES **10048.2 E; 168279.2 N**

PROJECT No **FG5388** SURFACE R.L. **4.13** DATE STARTED **16/2/05** DATUM **SETP**

JOB No **-----** DATUM **AHD** DATE COMPLETED **18/2/05** DRILLER **R&D DRILLING PTY LTD**

DEPTH (m)	R.L. (m)	AUGER Casing Wash Boring Core Drilling	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
0	4.13														
1						ESTUARINE WEATHERED OC CRUST Dark grey to mottled grey, slightly moist to mainly dry, stiff silty clay. Some organics in the upper area.			OL				18/02/05	1,3,7 N=10	SPT
2	2.53					ESTUARINE SILTY CLAY Dark grey to black, moist, very soft to soft. High plasticity.									
3									OH					RW, 1 N<1	SPT
4															
5	-0.87					ALLUVIAL SAND Grey brown to brown, wet, medium dense becoming loose with depth. Medium grained sand, some shell fragments.								RW, 1 N<1	SPT
6														4,5,6 N=11	SPT
7															
8									SP					1,6,4 N=10	SPT
9														3,2,3 N=5	SPT
10	-5.87														

REMARKS SPT N values in clayey gravel can overestimate density due to influence of coarser size gravel particles. Defect angles have been measured with respect to a horizontal plane.

LOGGED BY
A. DISSANAYAKE (DISS)



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No BH23

SHEET 2 of 5

REFERENCE No H9572

PROJECT GATEWAY BRIDGE DUPLICATION FOUNDATION INVESTIGATION - GATEWAY UPGRADE PROJECT

LOCATION PIER 11 - DOWN STREAM END COORDINATES 10048.2 E; 168279.2 N

PROJECT No FG5388 SURFACE R.L. 4.13 DATE STARTED 16/2/05 DATUM SETP

JOB No DATUM AHD DATE COMPLETED 18/2/05 DRILLER R&D DRILLING PTY LTD

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	ROD () %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH							DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS	
									BT	VI	IM	J	VL	EL						
10	-5.87					ALLUVIAL SAND Becoming very loose along the profile.													1,1,2 N=3	SPT
11								SP												
12	-7.37					SILTY SAND / SANDY SILT Grey brown to brown, wet, becoming very loose. Fine to medium grained sand.													RW, - N<1	SPT
13								SM												
14	-9.87					ESTUARINE SILTY CLAY Dark grey to black, moist, very soft.													RW, - N<1	SPT
15								OH											RW, - N<1	SPT
16	-11.37					SILTY SAND Grey brown to brown, wet, mainly very loose. Fine grained sand, minor shell content.													1,RW, - N<1	SPT
17								SM												
18	-14.37																		1,RW, - N<1	SPT
19						SILTY SAND / SAND Dark grey to dark brown, wet, medium dense, becoming loose with depth.														
20	-15.87							SM-SP											6,7,7 N=14	SPT

REMARKS SPT N values in clayey gravel can overestimate density due to influence of coarser size gravel particles. Defect angles have been measured with respect to a horizontal plane.

LOGGED BY
A. DISSANAYAKE (DISS)



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No BH23

SHEET 3 of 5

REFERENCE No H9572

PROJECT GATEWAY BRIDGE DUPLICATION FOUNDATION INVESTIGATION - GATEWAY UPGRADE PROJECT

LOCATION PIER 11 - DOWN STREAM END COORDINATES 10048.2 E; 168279.2 N

PROJECT No FG5388 SURFACE R.L. 4.13 DATE STARTED 16/2/05 DATUM SETP

JOB No ----- DATUM AHD DATE COMPLETED 18/2/05 DRILLER R&D DRILLING PTY LTD

DEPTH (m)	R.L. (m)	AUGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH kN/m ²	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
20	-15.87					SILTY SAND / SAND As above. Frequent very loose interbeds, fine sand becoming medium with depth.								
21													4.5,6 N=11	SPT
22													RW, 7.1 N<1	SPT
23														
24													1.2,6 N=8	SPT
25								SM- SP					RW, 7.1 N<1	SPT
26														
27													5.4,1 N=5	SPT
28													5.8,2 N=10	SPT
29														
30	-25.87												1.5,2 N=7	SPT

REMARKS SPT N values in clayey gravel can overestimate density due to influence of coarser size gravel particles. Defect angles
have been measured with respect to a horizontal plane.

LOGGED BY
A. DISSANAYAKE (DISS)



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No **BH23**

SHEET **4** of **5**

REFERENCE No **H9572**

PROJECT GATEWAY BRIDGE DUPLICATION FOUNDATION INVESTIGATION - GATEWAY UPGRADE PROJECT

LOCATION PIER 11 - DOWN STREAM END COORDINATES 10048.2 E; 168279.2 N

PROJECT No FG5388 SURFACE R.L. 4.13 DATE STARTED 16/2/05 DATUM SETP

JOB No DATUM AHD DATE COMPLETED 18/2/05 DRILLER R&D DRILLING PTY LTD

DEPTH (m)	R.L. (m)	ALGER CASING WASH BORING CORE DRILLING	RQD (%)	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
30	-25.87					SAND AND GRAVEL Grey to grey brown, wet, medium dense. Sub-angular to sub-rounded quartzitic and lithic fragments sizing up to 50mm.							
31												Gravel band	8,8,5 N=13 SPT
32												Gravel band	
33							GP-GM						5,6,6 N=12 SPT
34													26,22,19 N=41 SPT
35	-30.87					GRAVELLY SANDY CLAY Brown, moist, hard. Sub-angular to sub-rounded quartzitic and lithic fragments up to 50mm.							9,8,12 N=20 SPT
36							CL						
37	-32.87					SANDSTONE HW : Generally exhibits engineering properties of orange to green, moist, very dense silty sand.		HW					20,30/95,- N=50 SPT
38	-33.87					MUDSTONE HW: Dark grey to black, slightly moist, hard silty clay. Highly fissured with some cubic structures.		HW					30/125,- N=50 SPT
39													
40	-35.37				(25)	INTERBEDDED SANDSTONE & MUDSTONE SW : (See below).		SW					

REMARKS SPT N values in clayey strata can overestimate density due to influence of coarser size gravel particles. Defect angles have been measured with respect to a horizontal plane.

LOGGED BY
A. DISSANAYAKE (DISS)



**Queensland
Government**

Department of
Main Roads

ENGINEERING BOREHOLE

FOR GEOTECHNICAL TERMS AND
SYMBOLS REFER FORM F:GEOT 017/2-2004

BOREHOLE No **BH23**

SHEET **5** of **5**

REFERENCE No **H9572**

PROJECT **GATEWAY BRIDGE DUPLICATION FOUNDATION INVESTIGATION - GATEWAY UPGRADE PROJECT**

LOCATION **PIER 11 - DOWN STREAM END** COORDINATES **10048.2 E; 168279.2 N**

PROJECT No **FG5388** SURFACE R.L. **4.13** DATE STARTED **16/2/05** DATUM **SETP**

JOB No DATUM **AHD** DATE COMPLETED **18/2/05** DRILLER **R&D DRILLING PTY LTD**

DEPTH (m)	R.L. (m)	USC CORE RECORDING CORE RECORDING	RQD (%)	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
40	-35.87				INTERBEDDED SANDSTONE & MUDSTONE SW : Pale grey to black, laminated and bedded, low to medium strength with occasional high strength bands. Defects - Frequent lamination partings 30°-60° (5-10/m). - Joints @ 80° (1/m). - Broken zones <100mm.							Is(50)=0.45 MPa Is(50)=0.74 MPa	x	
41	-37.37		100 (38)			SW						Is(50)=0.83 MPa Is(50)=1.09 MPa	o	x
42	-38.47		100 (60)		Core has been generally broken between 40.80m and 41.5m SANDSTONE FINE TO MEDIUM GRAINED, LAMINATED SEDIMENTARY ROCK. SW : Pale grey to white, low to medium strength. Defects - Joints at 50-60° (2-3/m). - Joints at 80° (1/m). - Some mudstone (<50mm) interbeds.		SW					Is(50)=0.58 MPa Is(50)=0.16 MPa	x	o
43			100 (32)		MUDSTONE FINE GRAINED THINLY LAMINATED SEDIMENTARY ROCK. MW : Dark grey to black, thinly laminated, nearly brown, very low to low strength. Occasional high strength sandstone interbeds up to 200mm. Defects - Frequent lamination partings 35° (>10/m). - Broken and weak zones >0.5m.							Is(50)=0.87 MPa	o	
44			100 (16)			MW						High strength sandstone interbed Is(50)=2.75 MPa Is(50)=1.93 MPa	x	o
45			100 (0)		Core has been generally broken and altered throughout.							High strength sandstone interbed		
46	-41.67		72 (88)		Becoming very weak below 45.10m.							High strength sandstone interbed		
47	-42.67		100		SANDSTONE MEDIUM TO COARSE GRAINED, MASSIVE CALCAROUSLY CEMENTED SEDIMENTARY ROCK. SW : Pale grey to white, mainly medium to high strength.		SW					Very low to low strength rock kernels in high plastic clay		
48					Defects - Joints at 50° (2-3/m). - Broken zones <100mm. Borehole terminated at 46.8m							Broken zone Is(50)=1.52 MPa Is(50)=0.46 MPa Is(50)=0.74 MPa Is(50)=0.58 MPa Is(50)=0.85 MPa Is(50)=0.61 MPa	x	o
49												Broken zone		
50														

REMARKS SPT N values in clayey gravel can overestimate density due to influence of coarser size gravel particles. Defect angles have been measured with respect to a horizontal plane.

LOGGED BY
A. DISSANAYAKE (DISS)

Project: **Gateway Bridge Duplication Investigation**

Borehole No: **BH 23**

Start Depth: 39.50m

Finish Depth: 46.80m

Project No: FG5388

H No: 9464

