

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

MAIN ROADS DEPARTMENT

H422

Form 23ZL
(P/4/66)

DRILLING REPORT

PROJECT .. WOOLLOONGABBA INTERCHANGE

PROJECT No. 1/21

DISTRICT No. 1 SHIRE .. BRISBANE CITY

HOLE No. 5

ROAD..... DIBLEY STREET

JOB No.

LOCATION.. Dibley St. 14'6 W. of eastern

RL DATUM .. B.C.C.

alignment and 24' S. of southern alignment...
of Abington St.

COLLAR 7

TYPE AND SIZE OF DRILLING .. 0-16.5 2" Hollow

GROUND SURFACE.. ~~29.6~~ 40.0

Auger, 16.5-29.0 AXM. Diamond Drilling

ROCK SURFACE

BOTTOM OF HOLE... ~~29.6~~ 11.0

DATE DRILLED 14-15th April, 1966

WATER TABLE

DEPTH 1"=5'	% CORE REC.	DIAGRAM	STRATA	DESCRIPTION OF SOIL ROCK	SAMPLE	
					No.	TYPE
			2.0 PAVEMENT	bitumen and gravel		
4.5			CLAY	red and grey mottled moist, stiff	5A	UD
5.8						
7.0						
7.4			HIGHLY WEATHERED CLAY : SHALES	light grey to fawn ironstained in part moist to slightly moist, very stiff. dip of bedding $< 5^{\circ}$ shale is silty in part and grades to sandstone in places	5B	UD
9.5						
10.8					5C	UD
12.0						
12.4					5D	UD
14.5						
14.8					5E	UD
16.5						
18.0	39					
20.0	62					
23.0	21		HIGHLY WEATHERED CONGLOMERATE	ironstained, loosely bonded by clayey material most recovered core gravel only 17.5-18.0 fine sandstone band 24.3-25.6 ironstained clayey pebbly sandstone		
25.0	87					
29.0	22					
				End of Hole		

DRILLER .. C.W. J.P. PLANT..... MRD Gemco 9467

REMARKS.....

DATE 19/4/66 C.H. Shipway. GEOLOGIST

APPROVED. *C.H. Shipway* DATE. 17/6/66.