#### **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the <u>Creative Commons Attribution 4.0 Licence</u> (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence". This licence does not apply to the Queensland Government logo or trademarks.

#### **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database http://qgd.org.au/



# ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95

: PACIFIC MOTORWAY LOGAN RIVER SERVICE ROAD BRIDGE FOUNDATION

BOREHOLE N	· ·	148
SHEET	:	1 OF 3
REFERENCE N	'n:	н8101

R.L.   ROD () t   MATERIAL   DESCRIPTION   STUDENT SPACES   STUDENT SPACES			SURFACE R.L. : 3.96			Di	RILLI	ER : Foundril ED : 3/9/97	
ORAMELY CLAY Fale spray to dark brown, dry to moist, firm, fine to coarse grained.  CL  11.11.9  N=22  SILTY CLAY Mottled brown, moist allum. High organic content; minor sand layers (10mm).  CH  SUPP-65kPa  Res Su=12kPa  Res Su=12kPa  Supp-0.5kPa  Peak Su=42kPa  Res Su=12kPa  CH  Supp-0.5kPa  Peak Su=1.25kPa Res Su=16.5kPa Res Su=16.5	R.L. (m) (m) (CONE DRILL COORE DRILL COTAING OTHERS	( ) <b>%</b>	MATERIAL .	П	INTACT	DEFECT	LOG	ADDITIONAL DATA	SAMPLES
Mottled brown, moist allum. High organic content; minor sand layers  O.21  SANDY SILTY CLAY Borwn to drak brown, wet, fine to coarse grained grading to soft, moist, slty clay. Peak Su-16.5kPa  CH  Supp-0.5kPa  CH  Supp-0.5kPa  Peak Su-16.5kPa  CH  Supp-0.5kPa  Peak Su-16.5kPa  CH  Supp-0.5kPa  Supp-0.5kPa  Peak Su-18.3kPa  Res Su-18.3kPa  Res Su-18.3kPa  Res Su-18.3kPa  Sc  SANDY CLAY/CLAYET SAND Dark brown to dark grey, wet firm allum. Righ organic content.  SC  SANDY CLAY/CLAYET SAND Dark brown to dark grey, firm to stiff alluvium. Low plasticity.  CL  Sandy Clay  Supp-130kPa  1.06  Supp-0.5kPa  Supp-0.5kPa			Pale grey to dark brown, dry to moist,						si
Borwn to drak brown, wet, fine to coarse grained grading to soft, moist, silty clay. Peat layers to 100mm thick.  CH  Supp=0.5kPa  Res Su=41.25kPa Res Su=16.5kPa  CH  Supp=0.5kPa  Peak Su=41.25kPa Res Su=16.5kPa  Supp=0.5kPa  Supp=0.5kPa  Res Su=16.5kPa  Peak Su=38.5kPa Res Su=18.3kPa Res Su=18.3kPa  Res Su=18.3kPa  Analy CLAY/CLAYEY SAND Dark brown to dark grey, firm to stiff alluvium. Low plasticity.  Sandy Clay  Supp=130kPa  2,4,5 N=9			Mottled brown, moist allum. High organic content; minor sand layers	СН			<b>\</b>	04/09/97 Peak Su=48kPa	U F
SILTY CLAY Dark brown to dark grey, wet firm allum. High organic content.  SC  SANDY CLAY/CLAYEY SAND Dark brown to dark grey, firm to stiff alluvium. Low plasticity.  Sandy Clay  Sandy Clay  Supp=130kpa  2,4,5 N=9  CL  3,4,5 N=9			Borwn to drak brown, wet, fine to coarse grained grading to soft, moist, silty	СН				Peak Su=41.25kPa Res Su=16.5kPa	F
SANDY CLAY/CLAYEY SAND Dark brown to dark grey, firm to stiff alluvium. Low plasticity.  CL  Sandy Clay Supp=130kPa  2,4,5 N=9  CL  3,4,5 N=9			Dark brown to dark grey, wet firm allum.	sc		-			F
-5.54			Dark brown to dark grey, firm to stiff	CL				2,4,5 N=9	s s
-6.04   GRAVELLY SAND (See next page)   SP   T			GRAVELLY SAND (See next page)	SP					s



### ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95

BOREHOLE NO: 148

SHEET: 2 OF 3

REFERENCE NO: H8101

PROJECT : PACIFIC MOTORWAY LOGAN RIVER SERVICE ROAD BRIDGE FOUNDATION LOCATION : Pier 9 Grid Ref. 19645e 139887n PROJECT No : MP1006 SURFACE R.L.: 3.96 DRILLER : Foundril DATUM : AHD DATE DRILLED : 3/9/97 ROD INTACT DEFECT R.L. ADDITIONAL DATA STRENGTH SPACING ()% (m) MATERIAL GER DRIL SING (mm) AND GRAPHIC TESTS CORE DESCRIPTION TEST RESULTS REC\* GRAVELLY SAND 8,10,12 SPT Pale brown to brown, wet, medium dense poorly graded alluvium. SP 6,9,12 N=21 SPT -9.29 SPT SILTY CLAY Brown to grey brown. very stiff alluvium. Moist stiff to Partly mottled; minor sand layers. 4,7,9 SPT СН 5,6,9 **N=1**5 -13.04 INTERBEDDED ARGILLITE AND GREYWACKE GREY TO BLUE GREY, FINE TO MEDIUM GRAINED BEDDED METASEDIMENTARY ROCK. 30/70 bedding mainly 30-40 degrees. N>50 XW: Pale grey to grey black, mottled in parts, generally exhibits engineering properties of very stiff clay/clayey XW silt grading to very dense clayey sand. HW: Heavily brown ironstaining through HW out. Defects greater than 60 degrees Clay band SW 15.54 100 FR: Is(50)=1.97MPa LOGGED BY REMARKS :

(c) State of Queensland (Department of Transport and Main Roads) 2020; GC-BY-4:0. Please note copyright and limitation of liability



## ENGINEERING BORELOG

FOR GEOTECHNICAL TERMS AND SYMBOLS REFER FORM BQF 075:191/95 BOREHOLE No : 148

SHEET : 3 OF 3

REFERENCE No : H8101

OB No :		SURFACE R.L. :				R: Foundril D: 3/9/97	
R.L. (m) HLG WHING	RQD ( ) %  CORE NEC%	MATERIAL DESCRIPTION	USC	MEATHERING DEFECT STRENGTH SPACING (mm) SPAC	GRAPHIC LOG	ADDITIONAL DATA  AND  TEST RESULTS	SAMPLES
-17.84	100	FR: Light brown ironstaining only a				Is(50)=2.26MPa Is(50)=3.40MPa	×
22	100	END OF HOLE					

