

COPYRIGHT NOTICE

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department and author as follows: "(c) *State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence, prepared by SMEC*". This licence does not apply to the Queensland Government logo or trademarks.

LIMITATION OF LIABILITY

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>

This log has been contributed to the Queensland Geotechnical Database with the permission of SMEC.



GEOTECHNICAL LOG OF NON-CORE DRILLHOLE

Borehole No: BH101

Sheet No: 1 OF 2

Project No: 3003659

Client: QDTMR

Project: Smith Olsen Detailed Design Geotech Investigation Co-ordinates System: UTM Zone 56

Feature: Easting: 534787.9m E





Location: Refer Location Plan Northing: 6906949.4m S

Surface RL (m): 47.53

Angle from Horz: 90

Direction: n/a

SMEC GOLD COAST BOREHOLE NON CORE LOG I:\PROJECTS\3003659\005_OPERATIONS\DD15 GEOTECHNICAL\INVESTIGATIONS\GINT FILES\SMITH - OLSEN BOREHOLES (CURRENT) GPJ 18/11/11

DRILLING							TESTING				SUBSTANCE										
Method	Support	Rate			Water	Sample	Depth (m)	Depth/RL	Type	Sample or Field Test	Graphic Log	USC Symbol	Description	Moisture	Consistency/ Density	Other Observations					
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17					
ATC	HQ Casing	-	-	-						10,11,12 N=23		ML	Clayey SILT: Firm, dark brown, some grass roots, some fine to medium gravel, dry, fill?	D	F	Cobbles have been drilled and redrilled up to several times indicating possible uncompacted pockets of fine material between boulders					
													SPT				47.53	S		GM	Silty GRAVEL: Medium dense, fine to coarse angular gravel (Fr-SW) pale brown silt, dry.
																	0.50				Trace of orange brown and dark grey clay fines
																	47.03				
																	47.70				
													SPT				46.83	S			Fine to medium.
																	46.73				
																	1.30				
																	46.23				
													SPT				1	S			Fine to coarse, some fine to medium grained sand with trace of clay fines, moist.
							2	2.00								Refer to Geotechnical Log of Cored Drillhole					
								3													
															</						

Notes (Instrumentation etc):

Contractor: GeoDrill

Commenced: 11/07/11

Logged By: ME/BD

Equipment: Hydropower Scout

Completed: 11/07/11

Checked By: AR

Basis of description and details of abbreviations are given on explanatory notes



GEOTECHNICAL INVESTIGATIONS LOG

Borehole No: BH101

Sheet No: 2 OF 2

Project No: 3003659

Client: QDTMR

Project: Smith Olsen Detailed Design Geotech Investigation Co-ordinates System: UTM Zone 56

Feature: E: 534787.9








Location: Refer Location Plan

N: 6906949.4

Surface RL (m): 47.53

Angle from Horz: 90

Direction: n/a

DRILLING					SUBSTANCE								TEST		DEFECTS									
Method	Water	TCR %	RQD %	Lift	Depth (m)	Depth/RL	Graphic Log	Description ROCK TYPE, mineralogy, grain size, colour, fabric, etc.	Weathering					Estimated Strength				Type	Result	Fracture Spacing (mm)			Description	
									EW	HW	MW	SW	FS	FR	EL	VL	L			M	H	VH	EH	20
1	2	3	4	5	6	7	8	9	10					11				12	13	14			15	16
NMLC					1			Refer to Geotechnical log of Non-cored Drillhole																
					2	2.00 45.53		Gravelly SILT and BOULDERS/COBBLES: Stiff, low plasticity, grey-brown, fine to coarse gravel (Siltstone), cobbles (angular to sub angular MW to SW Metasiltstone and Metasandstone) and boulders (MW-SW and Fr). Fill?																
	100	2.2																						
	100	2.4																						
	100	2.7				2.70 44.83		CORE LOSS (2.70m to 3.50m)																
	33																							
							3.50 44.03		Gravelly SILT and BOULDERS/COBBLES: Stiff, low plasticity, grey-brown, fine to coarse gravel (Siltstone), cobbles (angular to sub angular MW to SW Metasiltstone and Metasandstone) and boulders (MW-SW and Fr), fill?															
		3.9																						
	100	4.2																						
	100	4.4																						
	100	4.8																						
	100	5.2																						
							5.15 42.38		CORE LOSS (5.15m to 5.55m)															
	38						5.55 41.98			Gravelly SILT and BOULDERS/COBBLES: Stiff, low plasticity, grey-brown, fine to coarse gravel (Siltstone), cobbles (angular to sub angular MW to SW Metasiltstone and Metasandstone) and boulders (MW-SW and Fr), fill?														
																								
						7.40 40.13		CORE LOSS (7.40m to 7.60m)																
									Hole discontinued at 7.60m															
					8																			
					9																			

Notes (Instrumentation etc):

Contractor: GeoDrill

Commenced: 11/07/11

Logged By: ME/BD


Equipment: Hydropower Scout

Completed: 11/07/11


Checked By: AR

Basis of description and details of abbreviations are given on explanatory notes

SMEC GOLD COAST BOREHOLE CORE LOG I:\PROJECTS\3003659\005_OPERATIONS\DD15_GEOTECHNICAL\INVESTIGATIONS\GINT FILES\SMITH - OLSEN BOREHOLES (CURRENT).GPJ 18/11/11



Borehole Number		BH101	
Box	1	of	1
Depth	2.0m	to	7.6m
Project	Smith St & Olsen Av		
Number	3003659		
Client	QDTMR		



NOTES RELATING TO GEOTECHNICAL REPORTS AND SITE INVESTIGATION LOGS

GEOTECHNICAL REPORTS AND SITE INVESTIGATION LOGS

Geotechnical reports/logs are prepared by qualified personnel on the information supplied or obtained and are based on current engineering standards of interpretation and analysis.

Information may be gained from limited subsurface testing, surface observations, previous work, and is supplemented by knowledge of the local geology and experience of the range of properties that may exhibited by the materials present. For this reason, geotechnical reports should be regarded as interpretative rather than factual documents, limited to some extent by the scope of information on which they rely.

Where the report/log has been prepared for a specific purpose (e.g. design of a three-storey building), the information and interpretation may not be appropriate if the design is changed (e.g. a twenty-storey building). In such cases, the report/log and the sufficiency of the existing work should be reviewed by SMEC in the light of the new proposal.

Every care is taken with the report/log content; however, it is not always possible to anticipate or assume responsibility for the following conditions:

- Unexpected variations in ground conditions. The potential for this depends on the amount of investigative work undertaken.
- Changes in policy or interpretation by statutory authorities
- The actions of contractors responding to commercial pressures

If these occur, SMEC would be pleased to resolve the matter through further investigation, analysis or advice.

UNFORESEEN CONDITIONS

Should conditions encountered on site differ markedly from those anticipated from the information contained in the report/log, SMEC should be notified immediately. Early identification of site anomalies generally results in any problems being more readily resolved and allows re-interpretation and assessment of the implications for future work.

SUBSURFACE INFORMATION

Logs of a borehole, recovered core, test pit, excavated face, or cone penetration test are an engineering and/or geological interpretation of the subsurface conditions. The reliability of the logged information depends on the drilling/testing method, sampling/observation spacing's and the ground conditions. It is not always possible or economic to obtain continuous high-quality data. It should also be recognised that the volume of material observed or tested is only a fraction of the total subsurface profile.

Interpretation of subsurface information and application to design and construction must take into consideration the spacing of the test locations, the frequency of observations and testing, and the possibility that geological boundaries may vary between observation points.

Groundwater observations and measurements outside of specially designed and constructed piezometers should be treated with care for the following reasons:

- In low permeability soils groundwater may not seep into an excavation or bore in the short time it is left open.
- A localised perched water table may not represent the true water table.
- Groundwater levels vary according to rainfall events or season.
- Some drilling and testing procedures mask or prevent groundwater inflow.

The installation of piezometers and long-term monitoring of groundwater levels may be required to adequately identify groundwater conditions.