

## **COPYRIGHT NOTICE**

This geotechnical log and its associated data (the Document) is licensed by the Queensland Department of Transport and Main Roads under the [Creative Commons Attribution 4.0 Licence](#) (CC BY 4.0). When reusing the Document, in whole or in part, please attribute the Department as follows: "*(c) State of Queensland (Department of Transport and Main Roads) 2020, licensed under the CC BY 4.0 Licence*". This licence does not apply to the Queensland Government logo or trademarks.

## **LIMITATION OF LIABILITY**

The CC BY 4.0 Licence contains a comprehensive Disclaimer of Warranties and Limitation of Liability. In addition, please note that this Document was prepared for Departmental use only. Reuse of the Document by anyone for any other purpose could result in error and/or loss. You should obtain professional advice before making decisions based on the contents of the Document.

When reproducing any part of this Document, you must also reproduce this limitation of liability notice in addition to the italicised attribution statement above.

Retrieved from the Queensland Geotechnical Database <http://qgd.org.au/>



# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH09  
SHEET 1 of 2  
REFERENCE No H11019

PROJECT Moreton Bay Rail Link  
LOCATION Brays Road Rail Bridge 5, Ch.4300 COORDINATES 501413.0 E; 6985695.5 N  
PROJECT No FG5921 SURFACE R.L. 12.90m PLUNGE        DATE STARTED 7/6/11 GRID DATUM MGA94 Zone 56  
JOB No 250/120/3 HEIGHT DATUM AHD BEARING        DATE COMPLETED 7/6/11 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING OTHER CORE DRILLING	RQD ( ) %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC WEATHERING	INTACT STRENGTH	DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES TESTS
0	12.90		CORE REC %									
1				A	<b>Gravelly Sandy CLAY (Residual)</b> Pale grey to orange red brown, moist, very stiff to hard.  Sand fraction is medium to coarse grained.  Subangular, high strength quartzitic gravel fraction sizing <25mm.  Gravel fraction increases with depth.  Ferruginous iron concretionary nodules throughout.	(GC?)					Non-destructive drilling up to 1.5m (Based on Driller's logs only)	5,9,10 N=19 SPT
2	10.40			B	<b>CLAYSTONE</b> <b>Fine grained sedimentary rock mainly comprising clay-sized particles</b> <b>XW:</b> Generally exhibits the engineering properties of white, pale grey to grey, red brown, moist, very stiff to hard silty clay.						12/80mm, HB, HB	N>50 SPT
3				C	Medium to high plasticity.  Iron stained, ferruginous alterations (nodules).						8,14,17 N=31	SPT
4				D		XW					6,9,11 N=20	SPT
5				E							8,9,16 N=25	SPT
6				F							9,20,31 N>50	SPT
7	5.90		(73)		<b>HW:</b> Mottled white to grey, red brown, fine grained, laminated, very low strength.  Defects: - Drilling-induced lamination partings @ 0-5° (2/m) - Joint @ 15° (1/m)  Defect surfaces are planar, slightly rough, open, clay infilled or iron stained.	HW						
8	4.40		100 (83)		<b>SANDSTONE</b> <b>MW:</b>	MW					Is(50) = 0.05MPa Is(50) = 0.06MPa	x o
9												
10			100		(See over)						CLY band	

REMARKS \_\_\_\_\_

LOGGED BY  
BW / DC2



# ENGINEERING BOREHOLE LOG

FOR GEOTECHNICAL TERMS AND  
SYMBOLS REFER FORM F:GEOT 017/6-2010

BOREHOLE No BH09  
SHEET 2 of 2  
REFERENCE No H11019

PROJECT Moreton Bay Rail Link  
LOCATION Brays Road Rail Bridge 5, Ch.4300 COORDINATES 501413.0 E; 6985695.5 N  
PROJECT No FG5921 SURFACE R.L. 12.90m PLUNGE      DATE STARTED 7/6/11 GRID DATUM MGA94 Zone 56  
JOB No 250/120/3 HEIGHT DATUM AHD BEARING      DATE COMPLETED 7/6/11 DRILLER R&D Drilling Pty Ltd

DEPTH (m)	R.L. (m)	AUGER CASING OTHER CORE DRILLING	RQD ( ) %	CORE REC %	SAMPLE	MATERIAL DESCRIPTION	LITHOLOGY	USC	WEATHERING	INTACT STRENGTH					DEFECT SPACING (mm)	GRAPHIC LOG	ADDITIONAL DATA AND TEST RESULTS	SAMPLES	TESTS
										EH	VH	IN	N	J	VL	EL			
10	2.90																		
					(81)	<b>SANDSTONE</b> Fine to coarse grained, massive, poorly cemented sedimentary rock comprising mainly of sand-sized particles MW: Orange brown to grey, fine to medium grained, massive with laminated, low to medium strength.											Is(50) = 0.04MPa Is(50) = 0.06MPa	x	
11																	Is(50) = 0.41MPa Is(50) = 0.26MPa	x	
12					100 (88)	Defects: - Drilling induced lamination / bedding partings @ 0-5° (4/m) - Joint @ 85-90° (1/m)  Defect surfaces are generally planar, smooth, tight or open, with clay infill.	MW										Is(50) = 0.71MPa Is(50) = 1.07MPa DD = 2.00t/m³; MC = 9.8%; UCS=4.41MPa	x	UCS
13	-0.03				100 (90)	<b>Interbedded SILTSTONE and SANDSTONE</b> SW: Grey to dark grey, black, fine to medium grained, laminated, medium to mainly high strength.  Medium to high strength.											Carb bands Is(50) = 0.95MPa Is(50) = 1.71MPa	x	
14						Defects: - Lamination partings @ 0-5° (4/m)											DD = 2.43t/m³; MC = 2.4%; UCS=48.7MPa		UCS
15					100 (62)	Defect surfaces are close to medium spaced, planar, smooth, open and closed, with clay infill.	SW										Is(50) = 1.36MPa Is(50) = 3.11MPa	x	
16					100 (92)												15.6m: Co CLy pocket Is(50) = 0.78MPa Is(50) = 1.19MPa	x	
17																	Is(50) = 1.20MPa Is(50) = 2.22MPa  Is(50) = 1.05MPa  DD = 2.45t/m³; MC = 2.6%; UCS=55.2MPa	x	UCS
18	-4.60				100	Borehole terminated at 17.5m													
19																			
20																			

REMARKS \_\_\_\_\_

LOGGED BY  
BW / DC2


<b>Project Name</b>	<b>Moreton Bay Rail Link (MBRL)</b>		
<b>Project No</b>	FG5921	<b>Date</b>	07/06/11
<b>Borehole No</b>	BH 9	<b>TMR H No</b>	11019
<b>Location</b>	Bray's Rd Rail Bridge	<b>Start Depth (m)</b>	7.00
<b>Detail</b>	Structure	<b>Finish Depth (m)</b>	17.50
<b>Chainage</b>	4310 Approx	<b>Submitted By</b>	BW
<b>Remarks</b>			


0 100 200 300 400 500 600mm

SCALE 1:5

<b>Project Name</b>	<b>Moreton Bay Rail Link (MBRL)</b>		
<b>Project No</b>	FG5921	<b>Date</b>	07/06/11
<b>Borehole No</b>	BH 9	<b>TMR H No</b>	11019
<b>Location</b>	Bray's Rd Rail Bridge	<b>Start Depth (m)</b>	7.00
<b>Detail</b>	Structure	<b>Finish Depth (m)</b>	17.50
<b>Chainage</b>	4310 Approx	<b>Submitted By</b>	BW
<b>Remarks</b>			

0      100      200      300      400      500      600mm

SCALE 1:5